



The bridge to possible

[Data sheet](#)
Cisco public

Cisco 10GBASE X2 Modules

Contents

Product overview	3
Technical specifications	4
Standards	6
Dimensions	8
Warranty	8
Cisco environmental sustainability	9
Cisco Capital	9
Additional information	10

Product overview

The Cisco® 10GBASE X2 modules (Figure 1) offer customers a wide variety of 10 Gigabit Ethernet connectivity options for data center, enterprise wiring closet, and service provider transport applications.



Figure 1.
Cisco 10GBASE X2 and Xenpak modules

Main features of Cisco 10GBASE X2 modules include:

- Support 10GBASE Ethernet
- Hot-swappable input/output device plugs into an Ethernet X2 port of a Cisco switch or router to link the port with the network
- Provides flexibility of interface choice
- Supports “pay-as-you-populate” model
- Supports the Cisco quality identification (ID) feature that enables a Cisco switch or router to identify whether the module is certified and tested by Cisco
- Has optical interoperability with respective 10GBASE Xenpak, 10GBASE XFP and 10GBASE SFP+ modules on the same link

Cisco X2-10GB-CX4

The Cisco 10GBASE-CX4 Module supports link lengths of up to 15m on CX4 cable.

Cisco X2-10GB-T

The Cisco 10GBASE-T Module supports link lengths of up to 100m on CAT6A or CAT7 copper cable.

Cisco X2-10GB-LRM

The Cisco 10GBASE-LRM Module supports link lengths of 220m on standard Fiber Distributed Data Interface (FDDI) grade multimode fiber (MMF). To ensure that specifications are met over FDDI-grade, OM1 and OM2 fibers, the transmitter should be coupled through a mode conditioning patch cord. No mode conditioning patch cord is required for applications over OM3. For additional information on mode conditioning patch cord requirements please see:

https://www.cisco.com/en/US/prod/collateral/modules/ps5455/product_bulletin_c25-530836.html.

The Cisco 10GBASE-LRM Module also supports link lengths of 300m on standard single-mode fiber (SMF, G.652).

Cisco X2-10GB-LX4

The Cisco 10GBASE-LX4 Module supports link lengths of 300m on standard FDDI grade MMF. To ensure that specifications are met, the transmitter output should be coupled through a mode conditioning patch cord. For additional information on mode conditioning patch cord requirements please see:

https://www.cisco.com/en/US/prod/collateral/modules/ps5455/product_bulletin_c25-530836.html.

Cisco X2-10GB-SR

The Cisco 10GBASE-SR Module supports a link length of 26m on standard FDDI grade MMF. Using 2000 MHz*km MMF (OM3), up to 300m link lengths are possible. Using 4700 MHz*km MMF (OM4), up to 400m link lengths are possible.

Cisco X2-10GB-LR

The Cisco 10GBASE-LR Module supports a link length of 10 kilometers on standard single-mode fiber (SMF, G.652).

Cisco X2-10GB-ER

The Cisco 10GBASE-ER Module supports a link length of up to 40 kilometers on standard single-mode fiber (SMF, G.652).

Cisco X2-10GB-ZR

Supports link lengths of up to about 80 km on SMF. This interface is not part of the 10 Gigabit Ethernet standard but is built according to Cisco optical specifications.

Technical specifications

Platform Support

Cisco X2 modules are supported on Cisco switches and routers. For more details, refer to the document Cisco Xenpak/X2 Compatibility Matrix.

Connectors and Cabling

Connectors: Dual SC/PC connector (-SR, -LR, -LRM, -LX4, -ER, -ZR); InfiniBand 4x connector (-CX4); RJ-45 connector (-T).

Note: For optical X2 modules, only connections with patch cords with PC or UPC connectors are supported. Patch cords with APC connectors are not supported. All cables and cable assemblies used must be compliant with the standards specified in the standards section.

Table 1 provides cabling specifications for the Cisco X2 modules.

Table 1. X2 Port Cabling specifications

Cisco X2	Wavelength (nm)	Cable Type	Core Size (Microns)	Modal Bandwidth (MHz*km)	Cable Distance*
Cisco X2-10GB-CX4	-	CX4 (copper)	-	-	15m
Cisco X2-10GB-T	-	CAT6A/CAT7 (copper)	-	-	100m
Cisco X2-10GB-SR	850	MMF	62.5	160 (FDDI-grade)	26m
			62.5	200 (OM1)	33m
			50.0	400	66m
			50.0	500 (OM2)	82m
			50.0	2000 (OM3)	300m
			50.0	4700 (OM4)	400m
Cisco X2-10GB-LRM	1310	MMF	62.5	500	220m
			50.0	400	100m
			50.0	500	220m
		SMF	G.652	-	300m
Cisco X2-10GB-LX4	1310	MMF	62.5	500	300m
			50.0	400	240m
			50.0	500	300m
Cisco X2-10GB-LR	1310	SMF	G.652	-	10 km
Cisco X2-10GB-ER**	1550	SMF	G.652	-	40 km***

* Minimum cabling distance for -LR, -SR, -LX4, -ER modules is 2m, according to the IEEE 802.3ae standard, and minimum cabling distance for -LRM modules is 0.5m, according to IEEE 802.3aq standard.

** Requires 5 dB 1550 nm fixed loss attenuator for < 20 km. Attenuator is available as a spare. The part number is WS-X6K-5DB-ATT=.

*** Links longer than 30 km are considered engineered links.

Standards

- IEEE 802.3ae (-LR, -SR, -LX4, -ER)
- IEEE 802.3ak (-CX4)
- IEEE 802.3aq (-LRM)
- IEEE 802.3an (-T)

Table 2 shows the main optical characteristics for the Cisco X2 module. The Cisco X2-10GB-CX4 and X2-10GB-T are not optical modules and therefore are not listed in Table 2.

Table 2. Optical transmit and receive specifications

Product	Type	Transmit Power (dBm)*		Receive Power (dBm)*		Transmit and Receive Wavelength Range (nm)	
		Maximum	Minimum	Maximum	Minimum	Transmit	Receive
Cisco X2-10GB-SR	10GBASE-SR 850 nm MMF	-1**	-7.3	-1.0	-9.9	840 to 860	
Cisco X2-10GB-LRM	10GBASE-LRM 1310 nm MMF and SMF	0.5	-6.5	0.5	-8.4 (in average) and -6.5 (in OMA)***	1260 to 1355	
Cisco X2-10GB-LX4	10GBASE-LX4 WWDM 1300 nm MMF	-0.5 per lane	-6.75 per lane in OMA	-0.5 per lane	-14.25 per lane in OMA	Four lanes; overall range: 1269 to 1356	
Cisco X2-10GB-LR	10GBASE-LR 1310 nm SMF	0.5	-8.2	0.5	-14.4	1260 to 1355	1260 to 1565****
Cisco X2-10GB-ER	10GBASE-ER 1550 nm SMF	4.0	-4.7	-1.0	-15.8	1530 to 1565	1260 to 1565****

* Transmitter and receiver power is in average, unless specified.

** The launch power shall be the lesser of the class 1 safety limit or the maximum receive power. Class 1 laser requirements are defined by IEC 60825-1: 2001.

*** Both average and OMA specifications must be met simultaneously.

**** Even though the receiver can tolerate a wide wavelength range, the specifications are guaranteed for a signal within the transmit wavelength range.

Table 3 details optical specifications for the Cisco X2-10GB-ZR modules.

Table 3. X2-10GB-ZR optical parameters

Parameter	Symbol	Minimum	Typical	Maximum	Units	Notes and Conditions
Transmitter						
Transmitter wavelength		1530		1565	nm	
Side-mode suppression ratio	SMSR	30			dB	
Transmitter extinction ratio		9			dB	
Transmitter optical output power	P_{out}	0		4.0	dBm	Average power coupled into single-mode fiber
Receiver						
Receiver optical input wavelength		1530		1565	nm	The receiver can tolerate a wavelength range from 1260 to 1565, but the specifications are guaranteed for a signal received with the transmit wavelength range
Receiver damage threshold				-1	dBm	
Dispersion tolerance		0		1600	ps/nm	
Optical input power	P_{in}	-24.0		-7.0	dBm	At bit error rate (BER) = $10e^{-12}$ with IEEE 802.3 test pattern
Dispersion power penalty at 1600 ps/nm				3	dB	At bit error rate (BER) = $10e^{-12}$ with IEEE 802.3 test pattern

Note: Parameters are specified over temperature and at end of life unless otherwise noted. When shorter distances of single-mode fiber are used, an inline optical attenuator must be used to avoid overloading and damaging the receiver.

Dimensions

- Dimensions (D x W x H): 91mm x 36mm x 13.46mm. Cisco X2s typically weigh under 300 grams
- Environmental Conditions and Power Requirements
- The operating temperature range is between 0 and 70°C (32 to 158°F); storage temperature range is -40 to 85°C (-40 to 185°F)
- The maximum power consumption per Cisco X2 module is 4W

Warranty

- Standard warranty: 5 years
- Expedited replacement available via a Cisco SMARTnet® Service support contract

Table 4 provides the ordering information for Cisco X2 modules and related cables.

Table 4. Ordering Cisco X2 and respective cables

Description	Product Number
X2 Modules	
Cisco 10GBASE-LR X2 Module for SMF	X2-10GB-LR
Cisco 10GBASE-CX4 X2 Module for CX4 (copper) cable	X2-10GB-CX4
Cisco 10GBASE-SR X2 Module for MMF	X2-10GB-SR
Cisco 10GBASE-LRM X2 Module for MMF	X2-10GB-LRM
Cisco 10GBASE-LX4 X2 Module for MMF	X2-10GB-LX4
Cisco 10GBASE-ER X2 Module for SMF	X2-10GB-ER
Cisco 10GBASE-ZR X2 Module for SMF	X2-10GB-ZR
Cisco 10GBASE-T X2 Module for CAT6A/CAT7 copper cable	X2-10GB-T
Cables	
Mode conditioning patch cable 62.5u, dual SC connectors	CAB-GELX-625=
Mode conditioning patch cable 50u, dual SC connectors	CAB-MCP50-SC=
1m cable for 10GBase-CX4 module	CAB-INF-28G-1=
5m cable for 10GBase-CX4 module	CAB-INF-28G-5=
10m cable for 10GBase-CX4 module	CAB-INF-28G-10=
15m cable for 10GBase-CX4 module	CAB-INF-26G-15=

Regulatory and standards compliance

Standards:

- GR-20-CORE: Generic Requirements for Optical Fiber and Optical Fiber Cable
- GR-326-CORE: Generic Requirements for Single-Mode Optical Connectors and Jumper Assemblies
- GR-1435-CORE: Generic Requirements for Multifiber Optical Connectors

Safety:

- Laser Class 1 21CFR-1040 LN#50 7/2001
- Laser Class 1 IEC60825-1

Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environment Sustainability” section of Cisco’s [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environment Sustainability” section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	Materials
Information on electronic waste laws and regulations, including products, batteries, and packaging	WEEE compliance

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

Additional information

For more information about Cisco 10GBASE-X2 modules, contact your sales representative or visit:
<https://www.cisco.com>.

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)