

# Cisco CWDM-SFP10G-1470 Compatibility Matrix Datasheet



Click here to buy our  
compatible transceiver

[BUY NOW](#)

## Compatible Devices:

C9400  
C9500  
N5000  
N7000  
NCS5000  
NCS5500  
C6800  
N9300  
N3000  
C9300  
N9500  
N9200  
ASR9000  
ASR1000  
ASR903  
ASR920  
NCS4200  
C3850  
C3650  
NCS540  
NCS560  
C9200  
C9200L  
C9600  
C9300L  
IE3300  
N7700  
NCS520  
C8500  
C9300X  
C9400X  
C9200CX  
C9300LM

C9400

IE9300

ESS3300

## C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24T-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48T-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24P-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48P-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24UXG-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48PF-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2

## NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA-8CS1Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.2	IOS XR 7.2.2
A900-IMA-8Z-L	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N560-IMA-8Q/4L	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

## N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.1	NX-OS 9.2.1
N9K-C92300YC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.1	NX-OS 9.2.1

## ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-9001	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.2	IOS XR 5.2.2
ASR-9001-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.2	IOS XR 5.2.2
ASR-9000V-AC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.4	IOS XR 5.2.4
ASR-9000V-DC-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.4	IOS XR 5.2.4
ASR-9000V-DC-E	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.4	IOS XR 5.2.4
A9K-24X10GE-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.2	IOS XR 5.2.2
A9K-24X10GE-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.2	IOS XR 5.2.2

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-36X10GE-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.0	IOS XR 5.2.0
A9K-36X10GE-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.0	IOS XR 5.2.0
A9K-MPA-8X10GE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.2	IOS XR 5.2.2

Network Device Notes for above line :

• On MOD80 and MOD160.

A9K-24X10GE-1G-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
A9K-24X10GE-1G-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
A9K-24X10GE-1G-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
A9K-24X10GE-1G-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
A9K-48X10GE-1G-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
A9K-48X10GE-1G-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
A9K-48X10GE-1G-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
A9K-48X10GE-1G-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
A9K-MPA-20X10GE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.4.2	IOS XR 6.4.2

Network Device Notes for above line :

• On MOD200 and MOD400.

A9K-MPA-20X10GE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.4.2	IOS XR 64 Bit 6.4.2
-----------------	------------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------------	---------------------

Network Device Notes for above line :

• On MOD200 and MOD400.

A9K-400G-DWDM-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.3	IOS XR 5.3.3
A99-48X10GE-1G-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
A99-48X10GE-1G-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-TR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
ASR-9901	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9903-8HG-PEC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9903-8HG-PEC-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-48X10GE-1G-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
A99-48X10GE-1G-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
A9K-24X10GE-1G-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.2	IOS XR 64 bit 6.3.2
A9K-24X10GE-1G-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
A9K-MPA-8X10GE-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.2	IOS XR 5.2.2

Network Device Notes for above line :

• On MOD80 and MOD160.

A9K-MPA-20X10GE-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.4.2	IOS XR 6.4.2
--------------------	------------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

• On MOD200 and MOD400.

A9K-MPA-20X10GE-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.4.2	IOS XR 64 Bit 6.4.2
--------------------	------------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------------	---------------------

Network Device Notes for above line :

• On MOD200 and MOD400.

ASR-9901-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9K-48X10GE-1G-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.2	IOS XR 64 bit 6.3.2
A9K-48X10GE-1G-FC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2

## N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-F348XP-25	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	—

## NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540-ACC-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-ACC-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-16Z4G8Q2C-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540X-16Z4G8Q2C-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540-28Z4C-SYS-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540-28Z4C-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540X-12Z16G-SYS-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540X-12Z16G-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540-12Z20G-SYS-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540-12Z20G-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
N540X-8Z16G-SYS-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-8Z16G-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-6Z18G-SYS-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-6Z18G-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-FH-CSR-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
N540X-4Z14G2Q-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540X-4Z14G2Q-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-24Q8L2DD-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-FH-AGG-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.7.1	IOS XR 7.7.1
N540-6Z18G-SYS-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
N540-6Z18G-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
N540-6Z14S-SYS-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
N540X-16Z8Q2C-D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

## NCS520

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N520-4G4Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
N520-X-4G4Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
N520-20G4Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
N520-X-20G4Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1

## N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C36180YC-R	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N3K-C34180YC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.2	NX-OS 9.2.2
Network Device Notes for above line : • SFP Ports (1-48)													
N3K-C34200YC-SM	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2V)	NX-OS 9.2(2V)
Network Device Notes for above line : • SFP Ports (1-48).													

## C3650

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-12X48UZ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-24TD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48TD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-24PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-24PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-24PDM	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48FD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48PQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48PQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48TQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48TQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-8X24PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
WS-C3650-8X24UQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-12X48UQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-12X48UR	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48FQM	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E
WS-C3650-48FQ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0E	IOS XE 3.7.0E

## N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N5K-C5672UP-16G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(2)N1(1)	
N5K-C5672UP	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(2)N1(1)	

## IE3300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-3300-8T2X-E	CWDM-SFP10G-1470	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8U2X-A	CWDM-SFP10G-1470	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8U2X-E	CWDM-SFP10G-1470	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8U2X-A	CWDM-SFP10G-1470	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													

## N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-F348XP-23	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)
N77-M348XP-23L	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)DX(1)	NX-OS 7.3(0)DX(1)

## C8500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8500-12X4QC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-12X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-20X6C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.10.1

## C3850

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-48F	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	IOS XE 3.7.2
WS-C3850-48XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
WS-C3850-48T	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48P	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24P	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24T	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-12S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-24S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.0	IOS XE 3.7.0
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-12XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-4-10G network module													
WS-C3850-12XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-16XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-32XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
C3850-NM-2-10G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-4-10G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-8-10G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													

## C6800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-32P10G-XL	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-16P10G-XL	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-8P10G-XL	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-32P10G	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-16P10G	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-8P10G	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-SUP6T	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6800-SUP6T-XL	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6824-X-LE-40G	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6840-X-LE-40G	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6816-X-LE	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6832-X-LE	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
C6880-X-LE	CWDM-SFP10G-1530	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	

## N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required, Min SW Release ACI-N9KDK9-12.1(1).													
N9K-C93180YC-EX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.1	NX-OS 9.2.1
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C93180YC-FX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required. ___ c) QSP Ports (49 - 52) supports 40G breakout, Min SW Release ACI-N9KDK9-13.2(1).													
N9K-C93180YC-FX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.1	NX-OS 9.2.1
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C9348GC-FXP	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) SFP Ports (49-52). ___ b) QSFP Ports (53-54), QSA (CVR-QSFP-SFP10G) required, Min SW Release ACI-N9KDK9-13.1(2).													
N9K-C93240YC-FX2	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-60), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93240YC-FX2	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C9372PX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	—
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C9372PX-E	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	—



Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C9364C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required. ___ b) SFP Ports (65-66).													
N9K-C9332C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • a) QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required. ___ b) SFP Ports (33-34).													
N9K-C9332C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)
Network Device Notes for above line : • SFP Ports (33-34)													
N9K-C93360YCFX2	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
Network Device Notes for above line : • a) SFP Ports (1-96). ___ b) QSFP Ports (97-108), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93360YCFX2	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
Network Device Notes for above line : • SFP Ports (1-96). QSFP Ports (97-108): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93600CDGX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9316D-GX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364C-GX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3I)	ACI-N9KDK9-14.2(3I)
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C93180YCFX3S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YCFX3	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • Supported on ports 1-48 only.													
N9K-C93180YCFX3	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
Network Device Notes for above line : • Supported on ports 1-48 only.													
N9K-C93108TCFX3P	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TCFX3P	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C9332D-GX2B	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(3)	ACI-N9KDK9-15.2(3)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9348D-GX2A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364D-GX2A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9348GCFX3	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C9348GC-FX3	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C9348GC-FX3PH	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)

## C9200CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200CX-8P-2X2G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12P-2X2G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12T-2X2G	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-8UXG-2X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4
C9200CX-8UXG-2XH	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4

## ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR1001-X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR1002-HX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR1001-HX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
<b>Network Device Notes for above line :</b> • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
EPA-10X10GE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1

## IE9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-9320-22S2C4X-E	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-22S2C4X-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-9320-24T4X-E	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24T4X-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24P4X-E	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24P4X-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-16P8U4X-E	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-16P8U4X-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<b>Network Device Notes for above line :</b> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													

## N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9564PX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	—
<b>Network Device Notes for above line :</b> • <a href="#">Downlinks.</a>													
N9K-X9464PX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9732C-EX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-FX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1	ACI-N9KDK9-13.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9716D-GX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(1)	ACI-N9KDK9-15.1(1)
Network Device Notes for above line : • QSFP-DD Ports, QSA (CVR-QSFP-SFP10G) required.													

## C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9400-SUP-1XL	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-LC-24XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-SUP-1XL-Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
C9400-LC-48XS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
C9400-LC-24XY	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1
C9400-LC-12QC	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) required.													

## C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-12Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-24Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-8Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1

## C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-24													
C9500-24Y4C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-24; QSFP Ports 25-28: QSA (CVR-QSFP-SFP10G) required.													
C9500-48Y4C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-48													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-48Y4C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-48; QSFP Ports 49-52: QSA (CVR-QSFP-SFP10G) required.													
C9500-12Q	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-40X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-NM-8X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-16X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500X-60L4D	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													

## C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1
Network Device Notes for above line : • Uplink module for C9200-24P/48P/24T/48T													
C9200-NM-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
Network Device Notes for above line : • Uplink module for C9200-24PXG; C9200-48PXG													
C9200-NM-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
Network Device Notes for above line : • Uplink module for C9200-48PL													
C9200-NM-2Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
Network Device Notes for above line : • Uplink module for C9200L-24PXG-4X/2Y; C9200L-48PXG-4X/2Y													

## C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN													
C9300-NM-8X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1

## NCS4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4200-1T8LR-PS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.14.0S	
NCS4201-SA	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
NCS 4201-SA	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4200-8T-PS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.16.1S	
NCS4202-SA	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14

## ESS3300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ESS-3300-NCP-E	CWDM-SFP10G-1470	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
ESS-3300-NCP-A	CWDM-SFP10G-1470	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

## C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-48YL	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600-LC-48YL	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-40YL4CD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-40YL4CD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600X-LC-56YL4C	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	IOS XE 17.13.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													

## C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9400X-SUP-2XL	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

## C9300LM

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300LM-24U-4Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48U-4Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48UX-4Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48T-4Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1

## ASR920

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-920-10SZ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-12CZ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-12SZ-IM	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-24SZ-M	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-24SZ-IM	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-4SZ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-24TZ-M	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-12SZ	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
ASR-920-20SZ-M	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR-920-10SZ-PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-8S4Z-PD	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14

## NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5501	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-5501-SE	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NC55-MOD-A-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-12T-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MOD-A-SE-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A2-MOD-HD-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-SE-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A2-MOD-HX-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-SE-H-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A1-48Q6H	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NCS-55A1-24Q6H-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25

Network Device Notes for above line :

• For QSFP Ports, QSA (CVR-QSFP-SFP10G) required

NCS-55A1-24Q6H-SS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
-------------------	------------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

• For QSFP Ports, QSA (CVR-QSFP-SFP10G) required

NC55-32T16Q4H-A	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
-----------------	------------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-57C3-MOD-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NCS-57C3-MOD-SE-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NC57-36H6D-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC57-MOD-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NCS-57C1-48Q6-SYS	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
NC57-MPA-12L-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NC55-OIP-02	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.7.1	IOS XR 7.7.1
Network Device Notes for above line : • Supported on NCS-57C3 and NCS-55A2													
NC57-48Q2D-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NC57-48Q2D-SE-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NCS-57C1-48Q6D-S	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

## NCS5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5001	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.0.0	
NCS-5002	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.0.0	

## ASR903

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA8S1Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.14.0S	
A900-IMA8T1Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.14.0S	
A900-IMA2Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.14.0S	
A900-IMA8Z	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.16.1S	

## C9200L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200L-24P-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48P-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24T-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													



Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200L-48T-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PXG-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-2Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PXG-2Y	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PL-4X	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1