

Cisco QSFP-40G-CSR-S Compatibility Matrix Datasheet



Click here to buy our compatible transceiver

[BUY NOW](#)

Compatible Devices

C9400
 C9500
 N7000
 UCSC
 N9300
 N3000
 C9300
 N9500
 NCS540
 C9200
 C9600
 C9300L
 N9800
 N7700
 C9300X
 UCSX
 C9400X

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9300L-24UXG-2Q	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9300L-48UXG-2Q	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9300L-48UXG-2Q	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-F312FQ-25	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N7K-M324FQ-25L	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540-ACC-SYS	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540X-ACC-SYS	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540X-16Z4G8Q2C-A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540X-16Z4G8Q2C-D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540-28Z4C-SYS-A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540-28Z4C-SYS-D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540-FH-CSR-SYS	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540-24Q8L2DD-SYS	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540-FH-AGG-SYS	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N540X-16Z8Q2C-D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.7.1	IOS XR 7.7.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3264C-E	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N3K-C3132C-Z	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N3K-C3408-S	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Network Device Notes for above line : • Supported on 400G LEM and odd ports of 100G LEM.													
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N3K-C3432D-S	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

N9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9836DM-A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X98900CD-A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-24C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • When in use with C9600-SUP-1. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9600-LC-24C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	—
Network Device Notes for above line : • When in use with C9600X-SUP-2. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9600-LC-40YL4CD	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	—
Network Device Notes for above line : • When in use with C9600X-SUP-2. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9600-LC-40YL4CD	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	—
Network Device Notes for above line : • When in use with C9600-SUP-1. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9600X-LC-32CD	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	—
Network Device Notes for above line : • When in use with C9600X-SUP-2. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9600X-LC-56YL4C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	—
Network Device Notes for above line : • When in use with C9600X-SUP-2. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N77-F324FQ-25	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N77-M312CQ-26L	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N77-F430CQ-36	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9400X-SUP-2XL	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93180YC-EX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93180YC-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93180YC-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93240YC-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Network Device Notes for above line : • Uplinks. Breakout not supported. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93240YC-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Network Device Notes for above line : • Uplinks. Breakout not supported. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9336C-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9336C-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-EX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-EX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9364C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 1 to 64 only Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9364C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93360YC-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93360YC-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93216TC-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93216TC-FX2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93600CD-GX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93600CD-GX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9316D-GX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9316D-GX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9364C-GX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9364C-GX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3I)	ACI-N9KDK9-14.2(3I)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93180YC-FX3S	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93180YC-FX3	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93180YC-FX3	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9336C-FX2-E	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9336C-FX2-E	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(4)	ACI-N9KDK9-15.2(4)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-FX3P	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-FX3P	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9332D-GX2B	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(1q) F	NX-OS 10.2(1q) F
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9332D-GX2B	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(3)	ACI-N9KDK9-15.2(3)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9348D-GX2A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9348D-GX2A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9364D-GX2A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C9364D-GX2A	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-FX3	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93108TC-FX3	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-C93400LD-H1	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9732C-EX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9732C-EX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9736C-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9736C-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9736Q-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9736Q-FX	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.2(9h)	ACI-N9KDK9-13.2(9h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9400-8D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9400-16W	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
N9K-X9400-16W	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9400-SUP-1XL	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9400-SUP-1XL-Y	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9400-LC-12QC	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-NM-2C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
C9300X-NM-4C	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
Network Device Notes for above line : • Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y. Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													

UCSX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSX-FI-6536	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
UCSX-FI-6536-U	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
Transceiver Notes for above line : • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later													
UCS-FI-6536	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500-48Y4C	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500-12Q	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500-24Q	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500-NM-2Q	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500-32QC	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500-32C	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500X-28C8D	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
C9500X-60L4D	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	—
Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													

C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-2Q	QSFP-40G-CSRS	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
Network Device Notes for above line : <ul style="list-style-type: none"> • Uplink module for C9200L-24PXG-4X/2Y; C9200L-48PXG-4X/2Y Transceiver Notes for above line : <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Q	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	—
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													

UCSC

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSC-M-V5D200G	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • VIC 15238 <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
UCSC-M-V5D200G-D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	UCS Manager v4.3.1
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • VIC 15238 <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
UCSC-P-V5D200G	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • VIC 15235 <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
UCSC-P-V5D200G-D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	UCS Manager v4.3.1
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • VIC 15235 <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
UCSC-M-V5D200GV2	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	UCS Manager v4.3(2c)
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • VIC 15237 <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													
UCSC-M-V5D200GV2D	QSFP-40G-CSR-S	TMG	40 Gbps	QSFP+	440m	Duplex Fiber	MMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	UCS Manager v4.3(2c)
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • VIC 15237 <p>Transceiver Notes for above line :</p> <ul style="list-style-type: none"> • OM3: 300m; OM4: 400m; OM5: 440m • DOM support for V02 or later 													