



Click here to buy our
compatible transceiver

[BUY NOW](#)

Compatible Devices

C9400

C9500

N2000

N5000

N6000

N7000

UCSB

UCSC

CRS

15454W

NCS5000

NCS5500

NCS6000

FPRHIGH

FPRUHI

NCS4000

C6800

N9300

N3000

C9300

N9500

N9200

ASR9000

C6000

ASR1000

ASR903

NCS4200

C4500

C3850

C3650

C3560X

NCS540

NCS560

C9400
 C9200
 C9600
 C9300L
 N9800
 C9800
 N7700
 Intel
 Qlogic
 C8500
 C9300X
 UCSX
 C9400X
 CSF4200

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-24UXG-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
C9300L-48UXG-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1

NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N560-IMA-2C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1

N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3.1

Network Device Notes for above line :

• Uplinks only

N9K-C92300YC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I6.1	NX-OS-703I6.1
--------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	---------------	---------------

Network Device Notes for above line :

• Uplinks only

N9K-C9236C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I4.1	NX-OS-703I4.1
------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	---------------	---------------

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92304QC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70314.1	NX-OS-70314.1
N9K-C9272Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N9K-C92348GC-X	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1

ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-MPA-1X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 4.2.3	—
Network Device Notes for above line : • On MOD80 and MOD160.													
A9K-MPA-1X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200 and MOD400													
A9K-MPA-1X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	—
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-2X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 4.2.3	—
Network Device Notes for above line : • On MOD80 and MOD160.													
A9K-MPA-2X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200 and MOD400													
A9K-MPA-2X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	—
Network Device Notes for above line : • On MOD200 and MOD400.													
A99-8X100GE-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • With CVR-CPAK-QSFP40													
A99-8X100GE-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • With CVR-CPAK-QSFP40													
A9K-8X100GE-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • With CVR-CPAK-QSFP40													
A9K-8X100GE-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • With CVR-CPAK-QSFP40													
A9K-8X100GE-LB-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • Require CVR-CPAK-QSFP40.													
A9K-8X100GE-LB-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • Require CVR-CPAK-QSFP40.													
A9K-20HG-FLEX-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-20HG-FLEX-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-8HG-FLEX-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-8HG-FLEX-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A99-32X100GE-X-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A99-32X100GE-X-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A99-32HG-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-20HG-FLEX-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-8HG-FLEX-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
ASR-9903	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.3	IOS XR 64 Bit 7.1.3
A9903-20HG-PEC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.3	IOS XR 64 Bit 7.1.3
A9K-4HG-FLEX-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9K-4HG-FLEX-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-TR	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
ASR-9902	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1

Network Device Notes for above line :

- Maximum number of optics supported is 40

A9903-20HG-PEC-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.3	IOS XR 64 Bit 7.1.3
ASR-9903-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.3	IOS XR 64 Bit 7.1.3
ASR-9902-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1

Network Device Notes for above line :

- Maximum number of optics supported is 40

A9K-4HG-FLEX-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9K-8X100GE-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2

Network Device Notes for above line :

- With CVR-CPAK-QSFP40

A9K-MPA-2X40GE-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 4.2.3	—
-------------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	--------------	---

Network Device Notes for above line :

- On MOD80 and MOD160.

A9K-MPA-2X40GE-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
-------------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	---------------------	---------------------

Network Device Notes for above line :

- On MOD200 and MOD400

A9K-MPA-2X40GE-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	—
-------------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	--------------	---

Network Device Notes for above line :

- On MOD200 and MOD400.

A99-8X100GE-FC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
----------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

- With CVR-CPAK-QSFP40

CSF4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-X-NM-4X40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
												Firepower product datasheets, installation guides, and release notes for software configurations.	

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M206FQ-23L	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.2(12)	NX-OS 6.2(12)
N7K-F312FQ-25	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.2(12)	NX-OS 6.2(12)
N7K-M324FQ-25L	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Breakout not supported.													
N540-ACC-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Breakout not supported.													
N540X-ACC-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Breakout not supported.													
N540X-16Z4G8Q2C-A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540X-16Z4G8Q2C-D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540-28Z4C-SYS-A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540-28Z4C-SYS-D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540-FH-CSR-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-24Q8L2DD-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-24Q8L2DD-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
N540X-16Z8Q2C-D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

CRS

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
2X100GE-FLEX-40	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.1.3	IOS XR 5.1.3

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3232C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)X1(2)	NX-OS 7.0(3)X1(2)
N3K-C36180YC-R	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(1)	NX-OS 7.0(3)F3(1)
Network Device Notes for above line :													
• Breakout not supported													
N3K-C3132Q-40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U3(1)	NX-OS 6.0(2)U3(1)
N3K-C3132Q-40GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U4(1)	NX-OS 6.0(2)U4(1)
N3K-C3132Q-XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
N3K-C3132Q-V	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3172TQ-10GT	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U3(1)	NX-OS 6.0(2)U3(1)
N3K-C3172TQ-32T	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172PQ-10GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U3(1)	NX-OS 6.0(2)U3(1)
N3K-C3264Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)X1(2)	NX-OS 7.0(3)X1(2)
N3K-C3636C-R	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(4)	NX-OS 7.0(3)F3(4)
Network Device Notes for above line :													
• Breakout not supported													
N3K-C3264C-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N3K-C3132C-Z	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)
N3K-C34180YC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2.2	—
N3K-C3408-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2t)	NX-OS 9.2(2t)
Network Device Notes for above line :													
• Supported on 400G LEM only. Support on odd ports of 100G LEM starting from NX-OS 9.3.5.													
N3K-C3432D-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2t)	NX-OS 9.2(2t)
N3K-C34200YC-SM	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2V)	NX-OS 9.2(2V)

N9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9836DM-A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.3(1)	NX-OS 10.3(1)

C3650

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-12X48UZ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1

N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N55-C55XX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(2)	—
N55-M4Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(2)	—
N5K-C5672UP-16G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	—
N5K-C5672UP	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(1)N1(1)	—
N5K-C5648Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
N5600-M12Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
N5K-C5624Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	NX-OS 7.1(0)N1(1a)
N5K-C5696Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	NX-OS 7.1(0)N1(1a)
N5696-M12Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	—
N5K-C56128P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	—
N56-M24UP2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	NX-OS 7.0(2)N1(1)

N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)DX(1)	NX-OS 7.3(0)DX(1)
N77-F324FQ-25	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.2(12)	NX-OS 6.2(12)
N77-F430CQ-36	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.3(1)	NX-OS 8.3(1)

C8500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8500-12X4QC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-20X6C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1

Network Device Notes for above line :

- Breakout not supported

C3850

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C3850-NM-2-40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1

Network Device Notes for above line :

- Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.

WS-C3850-48XS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
---------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	---------------	---------------

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-48XS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	IOS XE 3.7.2

C6800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-32P10G-XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-16P10G-XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-8P10G-XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-32P10G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-16P10G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-8P10G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-SUP6T	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6800-SUP6T-XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
Network Device Notes for above line : • 4SQRA (CVR-4SFP10G-QSFP) required, 4x10G ports used.													
C6824-X-LE-40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6840-X-LE-40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6800-8P40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.5(1)SY	
C6800-8P40G-XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.5(1)SY	

C4500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X45-SUP9-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.10.1E	IOS XE 3.10.1E

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	NX-OS 7.0314.2
N9K-C93180YC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54.													
N9K-C93180YC-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
N9K-C93180YC-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54. Ports 49 - 52 supports 40G breakout from 13.2(1).													
N9K-C9348GC-FXP	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 53 to 54 only													
N9K-C9348GC-FXP	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	NX-OS 70317.1
Network Device Notes for above line : • Supported on ports 53 and 54 only.													
N9K-C93240YC-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.3	NX-OS 70317.3
Network Device Notes for above line : • Uplinks. Breakout not supported.													
N9K-C93240YC-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • Supported on ports 49-60													
N9K-C9336C-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03.17.3	—
N9K-C9336C-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1(2)	ACI-N9KDK9-13.1(2)
Network Device Notes for above line : • Supported on ports 1-36													
N9K-M12PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-M12PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2j)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink module.													
N9K-M6PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
N9K-M6PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2j)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink module.													
N9K-M6PQ-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1)	NX-OS 7.0(3)I2(1)
N9K-M6PQ-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink module.													
N9K-C9372TX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372TX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9372PX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372PX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C9372PX-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1)	NX-OS 7.0(3)I2(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372PX-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9332PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
N9K-C9332PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C93120TX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I1(2)	NX-OS 7.0(3)I1(2)
Network Device Notes for above line : • Uplinks only.													
N9K-C93120TX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.2(1i)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9372TX-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372TX-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.2(2g)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C93108TC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	NX-OS 7.03I4.2
N9K-C93108TC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54													
N9K-C93180LC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I6.1	NX-OS-703I6.1
N9K-C93180LC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports (1-25,27,29-32; 26 and 28 are hw-disabled). Breakout supported in ACI-N9KDK9-13.1(1)													
N9K-C93108TC-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I7.1	—
N9K-C93108TC-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2A	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54.													
N9K-C9364C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I7.2	NX-OS 703I7.2
N9K-C9364C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 1 to 64 only													
N9K-C9336PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2j)	ACI-N9KDK9-13.0(1)
N9K-C9332C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • Supported on ports 1-32													
N9K-C9332C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)
Network Device Notes for above line : • Supported on ports 1-32													
N9K-C93360YC-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
N9K-C93360YC-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93216TC-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
N9K-C93216TC-FX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
N9K-C93600CD-GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • Breakout supported on ports 25-36 only. Starting from ACI-N9KDK9-15.1(3) , breakout is also supported on odd ports from 1-24.													
N9K-C93600CD-GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
Network Device Notes for above line : • Breakout supported on ports 25-36 only. Starting NX-OS 9.3(5), breakout is also supported on odd ports from 1-24.													
N9K-C9316D-GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
N9K-C9316D-GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N9K-C9364C-GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N9K-C9364C-GX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3)	ACI-N9KDK9-14.2(3)
N9K-C93180YC-FX3S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Network Device Notes for above line : • SyncE: network device and optic combination tested.													
N9K-C93180YC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
Network Device Notes for above line : • SyncE: network device and optic combination tested.													
N9K-C93180YC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • SyncE: network device and optic combination tested for ACI-N9KDK9-15.2.x onwards.													
N9K-C93180YC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
Network Device Notes for above line : • SyncE: network device and optic combination tested.													
N9K-C9336C-FX2-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	—
N9K-C9336C-FX2-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(4)	ACI-N9KDK9-15.2(4)
Network Device Notes for above line : • Supported on ports 1-36													
N9K-C93108TC-FX3P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
N9K-C93108TC-FX3P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	—
N9K-C9332D-GX2B	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(3)	ACI-N9KDK9-15.2(3)
N9K-C9332D-GX2B	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(1q) F	NX-OS 10.2(1q) F
N9K-C9348D-GX2A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
N9K-C9348D-GX2A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
N9K-C9364D-GX2A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
N9K-C9364D-GX2A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
N9K-C9332D-H2R	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C9348GC-FX3PH	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C93108TC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
N9K-C93108TC-FX3	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C93400LD-H1	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F

ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
EPA-1X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.11
EPA-2X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.11

Intel

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Intel XL710	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	—	—

FPRUHI

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-NM-4X40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X97160YC-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • Uplinks only.													
N9K-X9636PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-X9564PX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only.													
N9K-X9564TX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only.													
N9K-X9636Q-R	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F2(1)	NX-OS 7.0(3)F2(1)
Network Device Notes for above line : • Breakout not supported													
N9K-X9636C-R	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F2(1)	NX-OS 7.0(3)F2(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • Breakout not supported													
N9K-X9636C-RX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(1)	NX-OS 7.0(3)F3(1)
Network Device Notes for above line : • Breakout not supported													
N9K-X9464PX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only													
N9K-X9464TX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only													
N9K-X9536PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-X9432PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-X9432C-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N9K-X9464TX2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I3.1	NX-OS 703I3.1
N9K-X9732C-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	NX-OS 7.03I4.2
N9K-X9732C-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3	ACI-N9KDK9-13.0(1)
N9K-X9736C-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(2)	NX-OS 7.0(3)I7(2)
N9K-X9736C-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
N9K-X9736C-EX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I6(1)	NX-OS 7.0(3)I6(1)
N9K-X9788TC-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03.I7.3	NX-OS 7.03.I7.3
Network Device Notes for above line : • Uplinks only.													
N9K-X9736PQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2)	ACI-N9KDK9-13.0(1)
N9K-X9732C-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	NX-OS 7.03I4.2
N9K-X96136YC-R	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N9K-X9736Q-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0.3I7.6	NX-OS 7.0.3I7.6
N9K-X9736Q-FX	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(1)	ACI-N9KDK9-14.1(1)
N9K-X9624D-R2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1(2)	NX-OS 10.1(2)
N9K-X9400-8D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
N9K-X9400-16W	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
N9K-X9400-16W	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)

C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9400-SUP-1XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-SUP-1XL-Y	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
C9400-LC-12QC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-NM-2C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-4C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1

Network Device Notes for above line :

- Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y.

UCSX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSX-FI-6536	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.2	UCS Manager v4.2.2
UCSX-FI-6536-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.2	UCS Manager v4.2.2
UCS-FI-6536	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
UCSX-FI-6454-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCSX-FI-64108-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-48Y4C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-12Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-24Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1
C9500-NM-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-32QC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-32C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500X-28C8D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9500X-60L4D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1

C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1

Network Device Notes for above line :

- Uplink module for C9200L-24PXG-4X/2Y; C9200L-48PXG-4X/2Y

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1

Network Device Notes for above line :

• Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN

NCS4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4200-2Q-P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 3.16	

NCS6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-F-SCSW	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.2.1	—

NCS4000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4K-4H-OPW-QC2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.22	IOS XR 6.1.22

C3560X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560X-24T	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-48T	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-24P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-48P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-48PF	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	

15454W

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS2K-MR-MXP-LIC	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	10.6.1	10.6.1
NCS2K-400G-XP	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	10.6.1	10.6.1

C9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9800-80-K9	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-1X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-2X40GE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-24C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600-LC-24C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-40YL4CD	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-40YL4CD	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600X-LC-32CD	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600X-LC-56YL4C	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	IOS XE 17.13.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													

C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2XL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

N6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N6K-C6004-96Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(1)	—
N6K-C6004-M12Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(2)	NX-OS 6.0(2)N1(2)
N6K-C6004-M12Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(2)	NX-OS 6.0(2)N1(2)
N6004-B-24Q	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(2)	NX-OS 6.0(2)N1(2)
N6K-C6001-64P	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(2)	—
N6K-C6001-64T	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(1)	—

N2000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N2K-C2348TQ-E	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	—
N2K-C2348TQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1)	—
N2K-C2348UPQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)N1(1)	NX-OS 7.0(3)N1(1)
N2K-C2348UPQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
N2K-C2332TQ	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(2)	—

Qlogic

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Qlogic QL45412HLCU-SP	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	—	—

C6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X6904-40G-2TXL	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	—

Network Device Notes for above line :

- SFP-10G ports with 4SQRA

FPRHIGH

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR4K-NM-4X40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR4K-XNM-4X40G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR4K-XNM-2X100G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR4K-XNM-4X200G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

UCSC

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSC-PCIE-C40Q-03	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v2.2(7b)	—
Network Device Notes for above line : • VIC 1385. For 6200 server fabric interconnect.													
UCSC-PCIE-C40Q-03	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	—
Network Device Notes for above line : • VIC 1385. For 6332 and 6332-16UP server fabric interconnect.													
UCSC-MLOM-C40Q-03	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v2.2(7b)	—
Network Device Notes for above line : • VIC 1387. For 6332 and 6332-16 Fabric Interconnect.													
UCSC-MLOM-C40Q-03	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	—
Network Device Notes for above line : • VIC 1387. For 6332 and 6332-16UP server fabric interconnect.													
UCSC-PCIE-C100-04	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.02a	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSC-MLOM-C100-04	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.02a	—
UCSC-PCIE-ID40GF	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS HUU 4.1(1a)	—
Network Device Notes for above line : • General Product ID: Intel XL710. Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-PCIE-QD40GF	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS HUU 4.1(1a)	—
Network Device Notes for above line : • General Product ID: Qlogic QL45412HLCU-SP. Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-M-V100-04	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.1	—
Network Device Notes for above line : • VIC 1477. For 6300 server fabric interconnect.													
UCSC-M-V5D200G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
Network Device Notes for above line : • VIC 15238													
UCSC-M-V5D200G-D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	UCS Manager v4.3.1
Network Device Notes for above line : • VIC 15238													
UCSC-P-V5D200G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
Network Device Notes for above line : • VIC 15235													
UCSC-P-V5D200G-D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	UCS Manager v4.3.1
Network Device Notes for above line : • VIC 15235													
UCSC-M-V5D200GV2	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	UCS Manager v4.3(2c)
Network Device Notes for above line : • VIC 15237													
UCSC-M-V5D200GV2D	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	UCS Manager v4.3(2c)
Network Device Notes for above line : • VIC 15237													

UCSB

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCS-FI-6332-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1	UCS Manager v3.1
UCS-FI-6332-16UP-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1	UCS Manager v3.1
UCS-IOM-2304	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	—
UCS-FI-6454	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-6454-U	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NC55-36X100G	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-24X100G-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-18H18F	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-24H12F-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NC55-36X100G-A-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.1	IOS XR 6.3.1
NCS-5501	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5501-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-55A1-36H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-55A1-24H	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.1	IOS XR 6.3.1
NC55-36X100G-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-55A1-36H-SE-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
NC55-MOD-A-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-4H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-4H-HD-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-1TH2H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MOD-A-SE-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A1-48Q6H	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NCS-55A1-24Q6H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NC55-MPA-4H-HX-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC57-24DD	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.0.2	IOS XR 7.0.2
NC57-18DD-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.0.2	IOS XR 7.0.2
NCS-55A1-24Q6H-SS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
NC55-32T16Q4H-A	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NC57-36H-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.2	IOS XR 7.2.2
NCS-57B1-6D24H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NCS-57B1-5D24-SE	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NC57-MPA-2D4H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

Network Device Notes for above line :

- In conjunction with NCS-57C3 platform

NC57-MPA-2D4H-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
-----------------	--------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

- In conjunction with NC57-MOD-S platform

NCS-57C3-MOD-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NCS-57C3-MOD-SE-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NC57-36H6D-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
NC57-MOD-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NCS-57C1-48Q6-SYS	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
NCS-57D2-18DD-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
NC57-48Q2D-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NC57-48Q2D-SE-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NCS-57C1-48Q6D-S	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

NCS5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5011	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.0	

ASR903

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA2F	QSFP-40G-LR4	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 3.16	