

Cisco QSFP-40G-LR4-S Compatibility Matrix Datasheet



Click here to buy our
compatible transceiver

[BUY NOW](#)

Compatible Devices

C9400

C9500

N2000

N5000

N6000

N7000

UCSB

UCSC

NCS1000

NCS5000

NCS5500

FPRHIGH

FPRUHI

C6800

N9300

N3000

C9300

N9500

N9200

ASR9000

ASR1000

C3850

C3650

C3560X

NCS540

NCS560

C9200

C9600

C9300L

N9800

C9800

N7700

Intel

C9400

Qlogic

8000 Series

C8500

C9300X

UCSX

C9400X

CSF4200

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-24UXG-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
C9300L-48UXG-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1

NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N560-IMA-2C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1

N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3.1

Network Device Notes for above line :

• Uplinks only

N9K-C92300YC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I6.1	NX-OS-703I6.1
--------------	----------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	---------------	---------------

Network Device Notes for above line :

• Uplinks only

N9K-C9236C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I4.1	NX-OS-703I4.1
N9K-C92304QC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 703I4.1	NX-OS-703I4.1
N9K-C9272Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N9K-C92348GC-X	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1

ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-MPA-1X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-1X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-2X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.4	IOS XR 5.3.4
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-2X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 5.3.4	IOS XR 5.3.4
Network Device Notes for above line : • On MOD200 and MOD400.													
A99-12X100GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
A99-12X100GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9K-4X100GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.6.1	IOS XR 64 Bit 6.6.1
A9K-4X100GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
A99-32X100GE-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A9K-16X100GE-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
ASR-9901	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9K-20HG-FLEX-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 20													
A9K-20HG-FLEX-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 20													
A9K-20HG-FLEX-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 20													
A9K-20HG-FLEX-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 8													
A9K-8HG-FLEX-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 8													
A9K-8HG-FLEX-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 8													
A99-32X100GE-X-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 32													
A99-32X100GE-X-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 32													
A99-32X100GE-X-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 32													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A99-32X100GE-X-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 32													
A9K-20HG-FLEX-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 20													
A9K-20HG-FLEX-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 20													
A9K-8HG-FLEX-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.9.1	IOS XR 64 Bit 7.9.1
Network Device Notes for above line : • Maximum number of optics supported is 8													
A99-16X100GE-X-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
ASR-9903	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
A9903-20HG-PEC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
A9K-4HG-FLEX-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9K-4HG-FLEX-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-TR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9903-20HG-PEC-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
ASR-9903-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
A9K-4HG-FLEX-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-12X100GE-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
A99-12X100GE-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A99-16X100GE-X-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
ASR-9901-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A99-32X100GE-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
A9K-16X100GE-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
A9K-MPA-2X40GE-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-2X40GE-FC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
Network Device Notes for above line : • On MOD200 and MOD400.													

CSF4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-X-NM-	QSFP-40G-LR4-S	TMG	40	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to	Y	Please	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
4X40G			Gbps							70C		refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M206FQ-23L	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(4)	NX-OS 6.1(4)
N7K-F312FQ-25	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.2(6)	NX-OS 6.2(6)
N7K-M324FQ-25L	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Breakout not supported.													
N540-ACC-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Breakout not supported.													
N540X-ACC-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Breakout not supported.													
N540X-16Z4G8Q2C-A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540X-16Z4G8Q2C-D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540-28Z4C-SYS-A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540-28Z4C-SYS-D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
N540-FH-CSR-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-24Q8L2DD-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-24Q8L2DD-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
N540X-16Z8Q2C-D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3232C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C36180YCR	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(1)	NX-OS 7.0(3)F3(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line :													
• Breakout not supported													
N3K-C3064PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U1(2)	—
N3K-C3064PQ-10GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U1(2)	—
N3K-C3064PQ-10GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
N3K-C3016Q-40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U1(2)	—
N3K-C3064TQ-32T	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U1(2)	—
N3K-C3064TQ-10GT	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U1(2)	—
N3K-C3132Q-40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
N3K-C3132Q-40GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
N3K-C3132Q-XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
N3K-C3132Q-V	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3172TQ-10GT	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
N3K-C3172TQ-32T	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172PQ-10GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172PQ-XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172TQ-XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C31108PC-V	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C31108TC-V	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C31128PQ-10GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
N3K-C3264Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3636C-R	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(4)	NX-OS 7.0(3)F3(4)
Network Device Notes for above line :													
• Breakout not supported													
N3K-C3264C-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N3K-C3132C-Z	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)
N3K-C34180YC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2.2	—
N3K-C3432D-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2t)	NX-OS 9.2(2t)
N3K-C34200YC-SM	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2V)	NX-OS 9.2(2V)

N9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9836DM-A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.3(1)	NX-OS 10.3(1)
N9K-X98900CD-A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)

C3650

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-12X48UZ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1

N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N55-C55XX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(2)	—
N55-M4Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(2)	—
N5K-C5672UP-16G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	—
N5K-C5672UP	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(1)N1(1)	—
N5K-C5648Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
N5600-M12Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
N5K-C5624Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	NX-OS 7.1(0)N1(1a)
N5K-C5696Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	NX-OS 7.1(0)N1(1a)
N5696-M12Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	—
N5K-C56128P	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	—
N56-M24UP2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	NX-OS 7.0(2)N1(1)

N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)DX(1)	NX-OS 7.3(0)DX(1)
N77-F324FQ-25	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.2(6)	NX-OS 6.2(8)
N77-M312CQ-26L	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)

C8500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8500-12X4QC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-20X6C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1

Network Device Notes for above line :

- Breakout not supported

C3850

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C3850-NM-2-40G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
WS-C3850-48XS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
WS-C3850-48XS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	IOS XE 3.7.2

C6800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-SUP6T	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
Network Device Notes for above line : • SFP-10G ports with 4SQRA													
C6800-SUP6T-XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	
Network Device Notes for above line : • SFP-10G ports with 4SQRA													
C6800-8P40G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.5(1)SY	
C6800-8P40G-XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS 15.5(1)SY	

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	NX-OS 7.0314.2
N9K-C93180YC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54.													
N9K-C93180YC-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
N9K-C93180YC-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54. Ports 49 - 52 supports 40G breakout from 13.2(1).													
N9K-C9348GC-FXP	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	NX-OS 70317.1
Network Device Notes for above line : • Supported on ports 53 and 54 only													
N9K-C9348GC-FXP	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 53 to 54 only													
N9K-C93240YC-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.3	NX-OS 70317.3
Network Device Notes for above line : • Uplinks. Breakout not supported.													
N9K-C93240YC-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • Supported on ports 49-60													
N9K-C9336C-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0317.3	—
N9K-C9336C-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1(2)	ACI-N9KDK9-13.1(2)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • Supported on ports 1-36													
N9K-M12PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-M12PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2j)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink module.													
N9K-M6PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
N9K-M6PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2j)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink module.													
N9K-M6PQ-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1)	NX-OS 7.0(3)I2(1)
N9K-M6PQ-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink module.													
N9K-C9372TX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372TX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9372PX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372PX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9372PX-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1)	NX-OS 7.0(3)I2(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372PX-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9332PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
N9K-C9332PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C93120TX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I1(2)	NX-OS 7.0(3)I1(2)
Network Device Notes for above line : • Uplinks only.													
N9K-C93120TX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.2(1i)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Uplink only.													
N9K-C9372TX-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
Network Device Notes for above line : • Uplinks only.													
N9K-C9372TX-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.2 (2g)	ACI-N9KDK9-13.0(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • Uplinks only.													
N9K-C93108TC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	NX-OS 7.0314.2
N9K-C93108TC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54													
N9K-C93180LC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70316.1	NX-OS-70316.1
N9K-C93180LC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports (1-25,27,29-32; 26 and 28 are hw-disabled). Breakout supported in ACI-N9KDK9-13.1(1)													
N9K-C93108TC-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
N9K-C93108TC-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2A	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 49-54.													
N9K-C9364C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 70317.2	NX-OS 70317.2
N9K-C9364C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • Supported on ports 1 to 64 only													
N9K-C9336PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2j)	ACI-N9KDK9-13.0(1)
N9K-C9332C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • Supported on ports 1-32													
N9K-C9332C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)
Network Device Notes for above line : • Supported on ports 1-32													
N9K-C93360YC-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
N9K-C93360YC-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
N9K-C93216TC-FX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
N9K-C93600CD-GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • Breakout supported on ports 25-36 only. Starting from ACI-N9KDK9-15.1(3) , breakout is also supported on odd ports from 1-24.													
N9K-C93600CD-GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
Network Device Notes for above line : • Breakout supported on ports 25-36 only. Starting NX-OS 9.3(5), breakout is also supported on odd ports from 1-24.													
N9K-C9316D-GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
N9K-C9316D-GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N9K-C9364C-GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N9K-C9364C-GX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3)	ACI-N9KDK9-14.2(3)
N9K-C93180YC-FX3S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
N9K-C93180YC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
N9K-C93180YC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
N9K-C93180YC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
N9K-C9336C-FX2-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	—
N9K-C9336C-FX2-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(4)	ACI-N9KDK9-15.2(4)
Network Device Notes for above line : • Supported on ports 1-36													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93108TC-FX3P	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
N9K-C93108TC-FX3P	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	—
N9K-C9332D-GX2B	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(3)	ACI-N9KDK9-15.2(3)
N9K-C9332D-GX2B	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(1q) F	NX-OS 10.2(1q) F
N9K-C9348D-GX2A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
N9K-C9348D-GX2A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
N9K-C9364D-GX2A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
N9K-C9364D-GX2A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
N9K-C9332D-H2R	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C9348GC-FX3PH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C93108TC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
N9K-C93108TC-FX3	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)

ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
EPA-1X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.11
EPA-2X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.11

Intel

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Intel XL710	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	—	—

FPRUHI

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-NM-4X40G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X97160YC-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • Uplinks only.													
N9K-X9636PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-X9564PX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only.													
N9K-X9564TX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only.													
N9K-X9636Q-R	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F2(1)	NX-OS 7.0(3)F2(1)
Network Device Notes for above line : • Breakout not supported													
N9K-X9636C-R	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F2(1)	NX-OS 7.0(3)F2(1)
Network Device Notes for above line : • Breakout not supported													
N9K-X9636C-RX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(1)	NX-OS 7.0(3)F3(1)
Network Device Notes for above line : • Breakout not supported													
N9K-X9464PX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only													
N9K-X9464TX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
Network Device Notes for above line : • Uplinks only													
N9K-X9536PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-X9432PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2b)	NX-OS 6.1(2)I2(2b)
N9K-X9432C-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N9K-X9464TX2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03I3.1	NX-OS 7.03I3.1
N9K-X9732C-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	NX-OS 7.03I4.2
N9K-X9732C-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3	ACI-N9KDK9-13.0(1)
N9K-X9736C-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(2)	NX-OS 7.0(3)I7(2)
N9K-X9736C-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
N9K-X9736C-EX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I6(1)	NX-OS 7.0(3)I6(1)
N9K-X9788TC-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03.I7.3	NX-OS 7.03.I7.3
Network Device Notes for above line : • Uplinks only.													
N9K-X9736PQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2)	ACI-N9KDK9-13.0(1)
N9K-X9732C-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	NX-OS 7.03I4.2
N9K-X96136YC-R	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9736Q-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0.3i7.6	NX-OS 7.0.3i7.6
N9K-X9736Q-FX	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(1)	ACI-N9KDK9-14.1(1)
N9K-X9624D-R2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.1(2)	NX-OS 10.1(2)
N9K-X9400-8D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
N9K-X9400-16W	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
N9K-X9400-16W	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)

C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9400-SUP-1XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-SUP-1XL-Y	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
C9400-LC-12QC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-NM-2C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-4C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1

Network Device Notes for above line :

- Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y.

UCSX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSX-FI-6536	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.2	UCS Manager v4.2.2
UCSX-FI-6536-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.2	UCS Manager v4.2.2
UCS-FI-6536	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
UCSX-FI-6454-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCSX-FI-64108-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-48Y4C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-12Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-24Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-NM-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-32QC	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-32C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500X-28C8D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9500X-60L4D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1

C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1

Network Device Notes for above line :

- Uplink module for C9200L-24PXG-4X/2Y; C9200L-48PXG-4X/2Y

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1

Network Device Notes for above line :

- Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN

C3560X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560X-24T	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-48T	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-24P	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-48P	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	
WS-C3560X-48PF	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	

C9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9800-80-K9	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
												information .	
C9800-1X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-2X40GE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-24C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600-LC-24C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-40YL4CD	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-40YL4CD	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600X-LC-32CD	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600X-LC-56YL4C	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	IOS XE 17.13.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													

C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9400X-SUP-2XL	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

N6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N6K-C6004-96Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(1)	—
N6K-C6004-M12Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(2)	NX-OS 6.0(2)N1(2)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N6004-B-24Q	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(2)	NX-OS 6.0(2)N1(2)
N6K-C6001-64P	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N1(2)	—

N2000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N2K-C2348TQ-E	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	—
N2K-C2348TQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1)	—
N2K-C2348UPQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)N1(1)	NX-OS 7.0(3)N1(1)
N2K-C2348UPQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
N2K-C2332TQ	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(2)	—

Qlogic

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Qlogic QL45412HLCU-SP	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	—	—

FPRHIGH

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR4K-NM-4X40G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	—
FPR4K-XNM-4X40G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	—
FPR4K-XNM-2X100G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR4K-XNM-4X200G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

8000 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
8201	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
8202	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
8800-LC-36FH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
8800-LC-48H	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
8201-32FH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
88-LC0-36FH-M	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
88-LC0-36FH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
8101-32FH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
88-LC0-34H14FH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.3	IOS XR 7.3.3
8202-32FH-M	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
8201-24H8FH	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
86-MPA-14H2FH-M	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
86-MPA-4FH-M	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1

UCSC

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSC-PCIE-C40Q-03	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v2.2(7b)	—
Network Device Notes for above line : • VIC 1385. For 6200 server fabric interconnect.													
UCSC-PCIE-C40Q-03	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	—
Network Device Notes for above line : • VIC 1385. For 6332 and 6332-16UP server fabric interconnect.													
UCSC-MLOM-C40Q-03	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v2.2(7b)	—
Network Device Notes for above line : • VIC 1387. For 6332 and 6332-16 Fabric Interconnect.													
UCSC-MLOM-C40Q-03	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	—
Network Device Notes for above line : • VIC 1387. For 6332 and 6332-16UP server fabric interconnect.													
UCSC-PCIE-C100-04	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.02a	—
UCSC-MLOM-C100-04	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.02a	—
UCSC-PCIE-ID40GF	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS HUU 4.1(1a)	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • General Product ID: Intel XL710. Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-PCIE-QD40GF	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS HUU 4.1(1a)	—
Network Device Notes for above line : • General Product ID: Qlogic QL45412HLCU-SP. Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-M-V100-04	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.1	—
Network Device Notes for above line : • VIC 1477. For 6300 server fabric interconnect.													
UCSC-M-V5D200G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
Network Device Notes for above line : • VIC 15238													
UCSC-M-V5D200G-D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	UCS Manager v4.3.1
Network Device Notes for above line : • VIC 15238													
UCSC-P-V5D200G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2.3
Network Device Notes for above line : • VIC 15235													
UCSC-P-V5D200G-D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	UCS Manager v4.3.1
Network Device Notes for above line : • VIC 15235													
UCSC-M-V5D200GV2	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	UCS Manager v4.3(2c)
Network Device Notes for above line : • VIC 15237													
UCSC-M-V5D200GV2D	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	UCS Manager v4.3(2c)
Network Device Notes for above line : • VIC 15237													

UCSB

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCS-FI-6332-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1	UCS Manager v3.1
UCS-FI-6332-16UP-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1	UCS Manager v3.1
UCS-IOM-2304	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	—
UCS-FI-6454	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-6454-U	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NC55-36X100G	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-24X100G-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-18H18F	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-24H12F-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NC55-36X100G-A-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.1	IOS XR 6.3.1
NCS-5501	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5501-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-55A1-36H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-55A1-24H	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.1	IOS XR 6.3.1
NC55-36X100G-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-55A1-36H-SE-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
NC55-MOD-A-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-4H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-4H-HD-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-1TH2H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MOD-A-SE-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A1-48Q6H	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NCS-55A1-24Q6H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NC55-MPA-4H-HX-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC57-24DD	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.0.2	IOS XR 7.0.2
NC57-18DD-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.0.2	IOS XR 7.0.2
NCS-55A1-24Q6H-SS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
NC55-32T16Q4H-A	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NC57-36H-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.2.2	IOS XR 7.2.2
NCS-57B1-6D24H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NCS-57B1-5D24-SE	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NC57-MPA-2D4H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

Network Device Notes for above line :

• In conjunction with NCS-57C3 platform

NC57-MPA-2D4H-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
-----------------	----------------	-----	---------	-------	------	--------------	-----	----------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

• In conjunction with NC57-MOD-S platform

NCS-57C3-MOD-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NCS-57C3-MOD-SE-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NC57-36H6D-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
NC57-MOD-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NCS-57C1-48Q6-SYS	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
NCS-57D2-18DD-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
NC57-48Q2D-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NC57-48Q2D-SE-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NCS-57C1-48Q6D-S	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

NCS5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5011	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.0	

NCS1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS1002-K9	QSFP-40G-LR4-S	TMG	40 Gbps	QSFP+	10km	Duplex Fiber	SMF	LC (UPC)	Optic	0 to 70C	Y	IOS XR 6.1.2	IOS XR 6.1.2