

Cisco QSFP-4X10G-LR-S Compatibility Matrix Datasheet



Click here to buy our compatible transceiver

BUY NOW

Compatible Devices:

C9500
 N2000
 N5000
 N6000
 N7000
 NCS1000
 15454W
 NCS5000
 NCS5500
 N9300
 N3000
 C9300
 N9500
 N9200
 ASR9000
 NCS540
 NCS560
 CBR8
 C9600
 C9300L
 N7700
 8000 Series
 C9300X

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.12.2	
C9300L-24UXG-2Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.1.1	
C9300L-48UXG-2Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.12.2	
C9300L-48UXG-2Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.1.1	

NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N560-IMA-2C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1

N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	—
Network Device Notes for above line : • Uplinks only. Supported on ports 50 and 52 only													
N9K-C9236C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	—
N9K-C92304QC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	—
Network Device Notes for above line : • Breakout supported on Port 1-16													
N9K-C9272Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	—
Network Device Notes for above line : • Supported on ports 37-71													

ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A99-12X100GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
A99-12X100GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.6.1	IOS XR 64 Bit 6.6.1
A9K-4X100GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
A9K-4X100GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.6.1	IOS XR 64 Bit 6.6.1
A99-32X100GE-TR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.1	IOS XR 64 Bit 6.5.1
A9K-16X100GE-TR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.1	IOS XR 64 Bit 6.5.1
ASR-9901	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9K-20HG-FLEX-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-20HG-FLEX-TR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-8HG-FLEX-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-8HG-FLEX-TR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A99-32X100GE-X-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A99-32X100GE-X-TR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A99-32HG-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A9K-20HG-FLEX-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-8HG-FLEX-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.15	IOS XR 64 Bit 7.1.15
A99-16X100GE-X-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.1	IOS XR 64 Bit 6.5.1
ASR-9903	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
A9903-20HG-PEC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
A99-10X400GE-X-TR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.5.2	IOS XR 64 Bit 7.5.2
A99-10X400GE-X-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.5.2	IOS XR 64 Bit 7.5.2
ASR-9902	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.5.1	IOS XR 64 Bit 7.5.1

Network Device Notes for above line :

- Supports maximum of 8 optics

A99-4T-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.5.2	IOS XR 64 Bit 7.5.2
A9903-20HG-PEC-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
ASR-9903-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.3.1	IOS XR 64 Bit 7.3.1
ASR-9902-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.5.1	IOS XR 64 Bit 7.5.1

Network Device Notes for above line :

- Supports maximum of 8 optics

A99-12X100GE-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
A99-12X100GE-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.6.1	IOS XR 64 Bit 6.6.1
A99-16X100GE-X-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.1	IOS XR 64 bit 6.5.1
ASR-9901-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A99-32X100GE-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.1	IOS XR 64 bit 6.5.1
A9K-16X100GE-FC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.1	IOS XR 64 bit 6.5.1

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M206FQ-23L	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 8.0	—
N7K-F312FQ-25	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(2)D1(1)	
N7K-M324FQ-25L	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	—

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540-ACC-SYS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-ACC-SYS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-16Z4G8Q2C-A	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540X-16Z4G8Q2C-D	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-28Z4C-SYS-A	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-28Z4C-SYS-D	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-24Q8L2DD-SYS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-FH-AGG-SYS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.7.1	IOS XR 7.7.1
N540X-16Z8Q2C-D	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

15454W

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS2K-MR-MXP-LIC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	10	10
NCS2K-400G-XP	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	10.6.1	10.6.1

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3232C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C36180YCR	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(4)	NX-OS 7.0(3)F3(4)
N3K-C3064PQ-10GX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
N3K-C3132Q-40GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	
N3K-C3132Q-40GX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	
N3K-C3132Q-XL	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	
N3K-C3132Q-V	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3172TQ-10GT	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	
N3K-C3172TQ-32T	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172PQ-10GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172PQ-XL	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C3172TQ-XL	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
N3K-C31108PC-V	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C31108TC-V	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	
N3K-C31128PQ-10GE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	

Network Device Notes for above line :

- Port breakout not supported

N3K-C3264Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- Only two 10G lanes per port when in breakout mode

N3K-C3636C-R	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(4)	NX-OS 7.0(3)F3(4)
N3K-C3264C-E	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N3K-C3132C-Z	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C34180YC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.2.2	—
N3K-C3464C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)

Network Device Notes for above line :
• QSFP Ports (1-64).

N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N5K-C5672UP-16G	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	—
N5K-C5672UP	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(1)N1(1)	
N5K-C5696Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(1)N1(1)	NX-OS 7.3(1)N1(1)
N5696-M12Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(1)N1(1)	

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-24C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1

Network Device Notes for above line :
• When in use with C9600-SUP-1.

C9600-LC-24C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
--------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	---------------	---------------

Network Device Notes for above line :
• When in use with C9600X-SUP-2. Breakout not supported

C9600-LC-40YL4CD	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
------------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	---------------	---------------

Network Device Notes for above line :
• When in use with C9600X-SUP-2. Breakout not supported

C9600-LC-40YL4CD	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.8.1	—
------------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	---------------	---

Network Device Notes for above line :
• When in use with C9600-SUP-1.

C9600X-LC-32CD	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
----------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	---------------	---------------

Network Device Notes for above line :
• When in use with C9600X-SUP-2. Breakout not supported

N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(2)D1(1)	NX-OS 7.3(2)D1(1)
N77-F324FQ-25	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(2)D1(1)	
N77-M312CQ-26L	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 8.3(1)	NX-OS 8.3(1)

N6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N6K-C6001-64P	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(1)N1(1)	
N6K-C6001-64T	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(1)N1(1)	

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	—
N9K-C93180YC-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 703I7.1	—
N9K-C9348GC-FXP	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5

Network Device Notes for above line :

- Supported on ports 53 and 54 only

N9K-C9336C-FX2	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I7.3	—
N9K-C9336C-FX2	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(6)	ACI-N9KDK9-14.2(6)

Network Device Notes for above line :

- Supported on ports 1-36

N9K-C9332PQ	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	—
-------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	-------------------	---

Network Device Notes for above line :

- Supported on ports (1-12, 15-26) only.

N9K-C93108TC-EX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	—
N9K-C93108TC-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 703I7.1	—
N9K-C9364C-GX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N9K-C93180YC-FX3S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
N9K-C93180YC-FX3	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
N9K-C93180YC-FX3	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
N9K-C9336C-FX2-E	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.1.1	—
N9K-C9336C-FX2-E	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(4)	ACI-N9KDK9-15.2(4)

Network Device Notes for above line :

- Supported on ports 1-36

N9K-C93108TC-FX3P	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 9.3.5	—
N9K-C9332D-GX2B	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.2(1q) F	—
N9K-C9348D-GX2A	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	—
N9K-C9364D-GX2A	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	—
N9K-C9332D-H2R	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	—
N9K-C9348GC-FX3	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	—
N9K-C9348GC-FX3PH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	—
N9K-C93108TC-FX3	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
N9K-C93108TC-FX3	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C93400LD-H1	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	—

N2000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N2K-C2348TQ-E	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.3(1)N1(1)	

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X97160YC-EX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)

Network Device Notes for above line :

• Uplinks only.

N9K-X9636PQ	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(2)	—
N9K-X9636Q-R	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(4)	NX-OS 7.0(3)F3(4)
N9K-X9636C-RX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)F3(4)	NX-OS 7.0(3)F3(4)
N9K-X9536PQ	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(2)	—
N9K-X9432PQ	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	—
N9K-X9432C-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	—
N9K-X9732C-EX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	—
N9K-X9736C-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(2)	—
N9K-X9736C-EX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I6(1)	—
N9K-X9788TC-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I7.3	—

Network Device Notes for above line :

• Uplinks only.

N9K-X9732C-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.03I4.2	—
N9K-X9736Q-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 7.0.3I7.6	—
N9K-X9736Q-FX	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(1)	ACI-N9KDK9-14.1(1)
N9K-X9400-8D	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
N9K-X9400-16W	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
N9K-X9400-16W	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-NM-2C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-4C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1

Network Device Notes for above line :

• Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y.

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • Breakout not supported													
C9500-48Y4C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • Breakout not supported													
C9500-12Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-24Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-NM-2Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • 10G breakout supported.													
C9500-32QC	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • Breakout not supported													
C9500-32C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500-32C	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1
Network Device Notes for above line : • Supports 10Gb/s data rate													
C9500X-28C8D	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9500X-60L4D	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Q	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN													

8000 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
8201	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.0.12	IOS XR 7.0.12
8202	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
8800-LC-36FH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
8800-LC-48H	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.0.12	IOS XR 7.0.12
8201-32FH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
88-LC0-36FH-M	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
88-LC0-36FH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
8101-32FH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
88-LC0-34H14FH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.3	IOS XR 7.3.3
8202-32FH-M	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
8201-24H8FH	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
86-MPA-14H2FH-M	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
86-MPA-4FH-M	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1

CBR8

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CBR-SUP-250G	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.7.1	IOS XE 16.7.1
Network Device Notes for above line : • Breakout supported.													
CBR-DPIC-2X100G	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1

NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NC55-36X100G	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.0.0	IOS XR 6.0.0
NC55-24X100G-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-18H18F	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
NC55-24H12F-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • 10G breakout supported.													
NC55-36X100G-A-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.3.1	IOS XR 6.3.1
Network Device Notes for above line : • 10G breakout supported.													
NCS-5501	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5501-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • 10G breakout supported.													
NCS-55A1-36H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-55A1-24H	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.3.1	IOS XR 6.3.1
NC55-36X100G-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
NCS-55A1-36H-SE-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
NC55-MOD-A-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
Network Device Notes for above line : • 10G breakout supported.													
NC55-MPA-4H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-4H-HD-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
Network Device Notes for above line : • 10G breakout supported.													
NC55-MPA-1TH2H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MOD-A-SE-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A1-48Q6H	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NCS-55A1-24Q6H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NC55-MPA-4H-HX-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC57-24DD	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.0.2	IOS XR 7.0.2
NC57-18DD-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.0.2	IOS XR 7.0.2
NCS-55A1-24Q6H-SS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NC55-32T16Q4H-A	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NC57-36H-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.2.2	IOS XR 7.2.2
NCS-57B1-6D24H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NCS-57B1-5D24-SE	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NC57-MPA-2D4H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

Network Device Notes for above line :

• In conjunction with NCS-57C3 platform

NC57-MPA-2D4H-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
-----------------	-----------------	-----	---------	-------	------	----------------	-----	--------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

• In conjunction with NC57-MOD-S platform

NCS-57C3-MOD-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NCS-57C3-MOD-SE-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NC57-36H6D-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
NC57-MOD-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NCS-57C1-48Q6-SYS	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
NC57-48Q2D-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NC57-48Q2D-SE-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NCS-57C1-48Q6D-S	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

NCS5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5011	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.0	

NCS1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS1002-K9	QSFP-4X10G-LR-S	TMG	40 Gbps	QSFP+	10km	Parallel Fiber	SMF	MPO-12 (APC)	Optic	0 to 70C	Y	IOS XR 6.1.2	IOS XR 6.1.2