

Cisco SFP-10G-ER Compatibility Matrix Datasheet



Click here to buy this
transceiver

[BUY NOW](#)

C2960X
C2960XR
C9400
C9500
N3500
N2000
N5000
N6000
N7000
UCSB
CRS
NCS1000
NCS5000
NCS5500
NCS6000
FPRHIGH
FPRUHI
C2960L
C3560CX
C6800
AIRCTU
FPRMID
C4900
N9300
N3000
C9300
N9500
N9200
ASR9000
ASR1000
ASR903
ASR901
ASR920

C2960X
NCS4200
ME3600X
ME3800X
C4500
C4500X
IE5000
C3850
C3750X
C3650
C3560X
NCS540
NCS560
CBR8
ASAHIGH
C9200
C9200L
C9600
C9300L
C9800
RPHYSHF
IE3300
N7700
C1000
NCS520
C8500
C8300
CGPON
C9300X
UCSX
ESS3000
C9400X
C9200CX
C9300LM
IE9300
FPRLOW
CSF4200
FPRMID3

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required.													
C9300L-24T-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48T-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24P-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48P-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24UXG-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-2Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required.													
C9300L-48PF-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2

RPHYSHF

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
RPHYSHELF_3X6	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.7.1	IOS XE 16.7.1
RPHYSHELF_6X12	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.7.1	IOS XE 16.7.1
HA-RPHY-6X12-LC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1

IE5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-5000-12S12P-10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)EB	IOS 15.2(2)EB
Network Device Notes for above line : • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													

ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-9001	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.1	IOS XR 4.2.1
A9K-4T16GE-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.0	IOS XR 5.3.0
A9K-4T16GE-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.0	IOS XR 5.3.0
ASR-9001-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.1	IOS XR 4.2.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-9922-RP-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.2	IOS XR 4.2.2
ASR-9922-RP-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.2	IOS XR 4.2.2
ASR-9000V-AC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
ASR-9000V-DC-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
ASR-9000V-DC-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
ASR-9000V-24-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.1.0	IOS XR 5.1.0
A9KV-V2-AC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
A9KV-V2-DC-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
A9KV-V2-DC-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
A9K-16T8-B	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.1	IOS XR 4.2.1
A9K-24X10GE-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.1	IOS XR 4.2.1
A9K-24X10GE-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.1	IOS XR 4.2.1
A9K-36X10GE-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.0	IOS XR 4.2.0
A9K-36X10GE-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.2.0	IOS XR 4.2.0
A9K-MPA-8X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.1	IOS XR 4.3.1

Network Device Notes for above line :

- On MOD80 and MOD160.

A9K-MPA-8X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------------	---------------------

Network Device Notes for above line :

- On MOD400

A9K-MPA-8X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------------	---------------------

Network Device Notes for above line :

- On MOD200

A9K-MPA-8X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

- On MOD200 and MOD400.

ASR-9900-RP-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
ASR-9900-RP-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.0	IOS XR 5.3.0
ASR-9900-RP-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.2	IOS XR 4.3.2
ASR-9900-RP-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.0	IOS XR 5.3.0
A9K-RSP880-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.0	IOS XR 5.3.0
A9K-RSP880-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.0	IOS XR 5.3.0
A9K-24X10GE-1G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-24X10GE-1G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-24X10GE-1G-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-24X10GE-1G-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-48X10GE-1G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-48X10GE-1G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-48X10GE-1G-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-48X10GE-1G-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-MPA-20X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.1	IOS XR 64 Bit 6.2.1

Network Device Notes for above line :

- On MOD400

A9K-MPA-20X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

- On MOD400.

A9K-MPA-20X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200													
A9K-400G-DWDM-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.1	IOS XR 64 Bit 6.2.1
A9K-400G-DWDM-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.3	IOS XR 5.3.3
A99-48X10GE-1G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
A99-48X10GE-1G-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
ASR-9901	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.4.1	IOS XR 64 Bit 6.4.1
ASR-9903	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.3	IOS XR 64 Bit 7.1.3
A9K-4HG-FLEX-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9K-4HG-FLEX-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-TR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
ASR-9902	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9903-8HG-PEC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
ASR-9903-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.1.3	IOS XR 64 Bit 7.1.3
ASR-9902-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9K-4HG-FLEX-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9903-8HG-PEC-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-48X10GE-1G-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
A99-48X10GE-1G-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
A9K-24X10GE-1G-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.2	IOS XR 64 bit 6.2.2
A9K-24X10GE-1G-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-MPA-8X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 4.3.1	IOS XR 4.3.1
Network Device Notes for above line : • On MOD80 and MOD160.													
A9K-MPA-8X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD400													
A9K-MPA-8X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.2	IOS XR 64 bit 6.3.2
Network Device Notes for above line : • On MOD200													
A9K-MPA-8X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-20X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.1	IOS XR 64 bit 6.2.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • On MOD400													
A9K-MPA-20X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.3.2	IOS XR 5.3.2
Network Device Notes for above line : • On MOD400.													
A9K-MPA-20X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.0.1	IOS XR 6.0.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD200													
ASR-9901-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.4.1	IOS XR 64 bit 6.4.1
A9K-48X10GE-1G-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.2	IOS XR 64 bit 6.2.2
A9K-48X10GE-1G-FC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2

CSF4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-4215	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4225	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4245	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M132XP-12	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.2.6	NX-OS 4.2.6
N7K-M132XP-12L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1	NX-OS 5.1
N7K-M224XP-23L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(1)	NX-OS 6.1(1)
N7K-F312FQ-25	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required.													
N7K-F132XP-15	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.2	NX-OS 5.2
N7K-F248XP-25	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(1)	NX-OS 6.0(1)
N7K-F248XP-25E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)	NX-OS 6.1(2)
N7K-F348XP-25	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(12)	NX-OS 6.2(12)
N7K-M348XP-25L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)
N7K-M324FQ-25L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540-ACC-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-ACC-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-16Z4G8Q2C-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-16Z4G8Q2C-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-28Z4C-SYS-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-28Z4C-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-12Z16G-SYS-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-12Z16G-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-12Z20G-SYS-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-12Z20G-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-8Z16G-SYS-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-8Z16G-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-6Z18G-SYS-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-6Z18G-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-FH-CSR-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-4Z14G2Q-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
N540X-4Z14G2Q-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
N540-24Q8L2DD-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-FH-AGG-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
N540-6Z18G-SYS-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
N540-6Z18G-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
N540-6Z14S-SYS-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
N540X-16Z8Q2C-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3232C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N3K-C36180YCR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N3K-C3064PQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)U2(2c)	NX-OS 5.0(3)U2(2c)
N3K-C3064PQ-10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)U2(2c)	NX-OS 5.0(3)U2(2c)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3064PQ-10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U2(1)	—
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3064PQ-10GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)U3(1)	NX-OS 5.0(3)U3(1)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3064PQ-10GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U2(1)	—
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3016Q-40GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U2(1)	—
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3064TQ-32T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U2(1)	—
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3064TQ-10GT	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U2(1)	—
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-40GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U2(1)	NX-OS 6.0(2)U2(1)
Network Device Notes for above line : • QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
N3K-C3132Q-40GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U4(1)	NX-OS 6.0(2)U4(1)
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-40GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U4(1)	NX-OS 6.0(2)U4(1)
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
Network Device Notes for above line : • For native SFP+ ports and with CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-V	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • For native SFP+ ports and with CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3172TQ-10GT	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U3(1)	NX-OS 6.0(2)U3(1)
Network Device Notes for above line : • QSFP Port: QSA (CVR-QSFP-SFP10G) required.													
N3K-C3172TQ-32T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U3(1)	NX-OS 6.0(2)U3(1)
Network Device Notes for above line : • QSFP Port: QSA (CVR-QSFP-SFP10G) required.													
N3K-C3172PQ-10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)U3(1)	NX-OS 6.0(2)U3(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • For QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N3K-C3172PQ-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
Network Device Notes for above line : • For QSFP Ports: CVR-QSFP-SFP10G adapter (QSA) is required.													
N3K-C3172TQ-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C31108PC-V	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
N3K-C31108TC-V	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N3K-C31128PQ-10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3264Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3264C-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N3K-C3132C-Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)
N3K-C34180YC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.2	—
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N3K-C34200YC-SM	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2V)	NX-OS 9.2(2V)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													

IE3300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-3300-8T2X-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8T2X-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-3300-8U2X-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

Network Device Notes for above line :
• When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.

IE-3300-8U2X-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---	--

Network Device Notes for above line :
• When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.

AIRCTU

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
AIR-CT5760-25-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
AIR-CT5760-50-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
AIR-CT5760-100-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
AIR-CT5760-250-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
AIR-CT5760-500-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
AIR-CT5760-1K-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
AIR-CT5760-HA-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	NX-OS 70314.2

Network Device Notes for above line :
• a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.

N9K-C93180YC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3(2)	ACI-N9KDK9-13.0(1)
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------------	--------------------

Network Device Notes for above line :
• a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required, Min SW Release ACI-N9KDK9-12.1(1).

N9K-C93180YC-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------	---

Network Device Notes for above line :
• a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.

N9K-C93180YC-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-13.0(1)
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------------	--------------------

Network Device Notes for above line :
• a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required. ___ c) QSP Ports (49 - 52) supports 40G breakout, Min SW Release ACI-N9KDK9-13.2(1).

N9K-C9348GC-FXP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	NX-OS 70317.1
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------	---------------

Network Device Notes for above line :
• Supported on ports 49 - 52 only

N9K-C9348GC-FXP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
-----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------------	--------------------

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • a) SFP Ports (49-52). ___ b) QSFP Ports (53-54), QSA (CVR-QSFP-SFP10G) required, Min SW Release ACI-N9KDK9-13.1(2).													
N9K-C93240YC-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.3	NX-OS 70317.3
Network Device Notes for above line : • SFP Ports (1-48). Breakout not supported.													
N9K-C93240YC-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-60), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336C-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1(2)	ACI-N9KDK9-13.1(2)
Network Device Notes for above line : • a) QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required. ___ b) QSFP Ports (1-30), 40G breakout supported.													
N9K-C9336C-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.03.17.3	NX-OS 7.03.17.3
Network Device Notes for above line : • QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9372PX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(1)	NX-OS 6.1(2)I3(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9372PX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C9372PX-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1)	NX-OS 7.0(3)I2(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9372PX-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C93108TC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70315.1	NX-OS 70315.1
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.0(1)	ACI-N9KDK9-12.0(1)
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180LC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180LC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required. Mode 1: 28 x 40G + 4 x 40G/100G (If top port is configured as 10G or 1G using QSA adapter; the bottom port also needs to be 10G or 1G to match the speed). Mode 2: 24 x 40G + 6 x 40G/100G (If top port is configured as 10G or 1G using QSA adapter; the bottom port also needs to be 10G or 1G to match the speed). Port 26 and 28 are disabled. Mode 3: 18 x 40G/100G (QSA is supported on all the 18 ports.)													
N9K-C93108TC-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	NX-OS 70317.1
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TC-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-12.2(2)
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C9364C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.2	NX-OS 70317.2
Network Device Notes for above line : • a) QSFP Ports (49-64), QSA (CVR-QSFP-SFP10G) required. ___ b) QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required, min SW release NX-OS 9.2.1.													
N9K-C9364C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required. ___ b) SFP Ports (65-66).													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C9396PX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2)	NX-OS 6.1(2)I2(2)
N9K-C9396PX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(2)	ACI-N9KDK9-13.0(1)
N9K-C9332C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • a) QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required. b) SFP Ports (33-34).													
N9K-C9332C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)
Network Device Notes for above line : • a) QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required. b) SFP Ports (33-34).													
N9K-C93360YC-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
Network Device Notes for above line : • a) SFP Ports (1-96). b) QSFP Ports (97-108), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93360YC-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
Network Device Notes for above line : • SFP Ports (1-96). QSFP Ports (97-108): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93216TC-FX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
Network Device Notes for above line : • QSFP Ports (97-108), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93600CD-GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9316D-GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364C-GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3)	ACI-N9KDK9-14.2(3)
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C93180YC-FX3S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested. b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-FX3	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested for ACI-N9KDK9-15.2.x onwards. b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-FX3	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested. b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336C-FX2-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Network Device Notes for above line : • QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336C-FX2-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(4)	ACI-N9KDK9-15.2(4)
Network Device Notes for above line : • a) QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required. b) QSFP Ports (1-30), 40G breakout supported.													
N9K-C93108TC-FX3P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TC-FX3P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C9332D-GX2B	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(3)	ACI-N9KDK9-15.2(3)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C9348D-GX2A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364D-GX2A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9348GC-FX3	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C9348GC-FX3PH	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C93108TC-FX3	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) or QSA (CVR-QSFP-SFP10G) is required													
N9K-C93108TC-FX3	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) or QSA (CVR-QSFP-SFP10G) is required													
N9K-C93400LD-H1	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F

ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR1001-X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.12.0a	
ASR1002-HX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2S	IOS XE 16.2S
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1001-HX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
EPA-10X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X97160YC-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • 1) SFP ports (1-48) 2) QSFP ports (49-52), QSA (CVR-QSFP-SFP10G) required.													
N9K-X9564PX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2)	NX-OS 6.1(2)I2(2)
Network Device Notes for above line : • Downlinks.													
N9K-X9464PX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2a)	NX-OS 6.1(2)I2(2a)
N9K-X9432PQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(1)	NX-OS 7.0(3)I5(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9464TX2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70315.1	NX-OS 70315.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-X9732C-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)15(2)	NX-OS 7.0(3)15(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9732C-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)17(2)	NX-OS 7.0(3)17(2)
Network Device Notes for above line : • QSFP Ports (1-36): QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1	ACI-N9KDK9-13.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-EX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)16(1)	NX-OS 7.0(3)16(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9788TC-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.03.17.3	NX-OS 7.03.17.3
Network Device Notes for above line : • QSFP Ports (49-52): QSA (CVR-QSFP-SFP10G) required													
N9K-X9732C-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)15(2)	NX-OS 7.0(3)15(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X96136YC-R	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N9K-X9736Q-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0.317.6	NX-OS 7.0.317.6
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736Q-FX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(1)	ACI-N9KDK9-14.1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9716D-GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-X9716D-GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(1)	ACI-N9KDK9-15.1(1)
Network Device Notes for above line : • QSFP-DD Ports, QSA (CVR-QSFP-SFP10G) required.													

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-12Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-2C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. QSA28 (CVR-QSFP28-SFP25G) can also be used from IOS XE 17.12.1. Uplink module for C9300X models only													
C9300X-24Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-8Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-4C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. QSA28 (CVR-QSFP28-SFP25G) can also be used from IOS XE 17.12.1. Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y.													

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-24													
C9500-24Y4C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-24; QSFP Ports 25-28: QSA (CVR-QSFP-SFP10G) required.													
C9500-48Y4C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-48													
C9500-48Y4C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-48; QSFP Ports 49-52: QSA (CVR-QSFP-SFP10G) required.													
C9500-12Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-24Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1a	IOS XE 16.5.1a
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-40X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-NM-2Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-32QC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-32C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-NM-8X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-16X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500X-28C8D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													
C9500X-60L4D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN													
C9300-NM-8X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1
C9300-NM-2Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN													

NCS4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4200-1T8LR-PS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.13.0S	
NCS4201-SA	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
NCS4200-8T-PS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.16.1S	
NCS4202-SA	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13

CGPON

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CGP-OLT-8T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	1.2.1.17	1.2.1.17
CGP-OLT-16T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	1.2.1.17	1.2.1.17

ME3600X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ME-3600X-24FS-M	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(52)EY	IOS 12.2(52)EY
Network Device Notes for above line : • SFP+ ports													
ME-3600X-24TS-M	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(52)EY	IOS 12.2(52)EY
Network Device Notes for above line : • SFP+ ports													

C4500X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4500X-32SFP+	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-F-32SFP+	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-40X-ES	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
C4KX-NM-8SFP+	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4500X-16SFP+	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG
WS-C4500X-F-16SFP+	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG
WS-C4500X-24X-ES	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG

C2960XR

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960XR-24TD-I	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-48TD-I	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-24PD-I	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-48LPD-I	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-48FPD-I	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1

C8300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8300-2N2S-4T2X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8300-1N1S-4T2X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C-NIM-1X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C-NIM-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.11.1	IOS XE 17.11.1

ASR901

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A901-6CZ-F-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SN H1	IOS 15.2(2)SN H1
Network Device Notes for above line : • SFP+ ports													
A901-6-CZ-FT-D	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SN H1	IOS 15.2(2)SN H1
Network Device Notes for above line : • SFP+ ports													
A901-6CZ-F-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SN H1	IOS 15.2(2)SN H1
Network Device Notes for above line : • SFP+ ports													
A901-6-CZ-FT-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SN H1	IOS 15.2(2)SN H1
Network Device Notes for above line : • SFP+ ports													

NCS5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5001	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.0.0	
NCS-5002	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.0.0	

ASAHIGH

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASA 5585-X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ASA 8.2.3	

NCS1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS1002-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required.

ASR903

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA8S1Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.13.0S	
A900-IMA8T1Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.13.0S	
A900-IMA2Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.13.0S	

Network Device Notes for above line :

- For ASR903/ASR907/NCS4200

A900-IMA2Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.14.0S	
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------	--

Network Device Notes for above line :

- For ASR920/NCS4201/NCS4202

A900-IMA8Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.16.1S	
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------	--

C9200L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200L-24P-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2

Network Device Notes for above line :

- On board - fixed uplinks

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200L-48P-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24T-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48T-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PXG-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-2Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PL-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1

C4900

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4948E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SG	IOS 15.0(2)SG
WS-C4948E-F	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SG	IOS 15.0(2)SG

NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA-8Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
A900-IMA-8CS1Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
A900-IMA-8Z-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N560-IMA-8Q/4L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	NX-OS 7.0(3)I3.1
N9K-C92160YC-X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7035.1	NX-OS 7035.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-C92300YC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70316.1	NX-OS 70316.1
N9K-C9236C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS-70315.1	
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-C9272Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.03(l)5.1	NX-OS 7.03(l)5.1
Network Device Notes for above line : • QSFP Port: QSA (CVR-QSFP-SFP10G) required. Supported on ports 37-71.													
N9K-C92348GC-X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1

CRS

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
40x10GE-WLO	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.1.1	IOS XR 5.1.1

NCS520

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N520-4G4Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
N520-X-4G4Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
N520-20G4Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
N520-X-20G4Z	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1

C3650

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-12X48UZ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-24TD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48TD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-24PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-24PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-24PDM	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48FD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48TQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48TQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-8X24PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
WS-C3650-8X24UQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-12X48UQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-12X48UR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48FQM	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48FQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE

N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N5K-C5672UP-16G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(1)N1(1)	NX-OS 7.0(1)N1(1)
N5K-C5672UP-16G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	

Network Device Notes for above line :

- QSA Ports: QSA (CVR-QSFP-SFP10G) is required.

N5K-C5672UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(1)N1(1)	NX-OS 7.0(1)N1(1)
-------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- For QSFP Ports: QSA (CVR-QSFP-SFP10G) is required

N5K-C5648Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required

N5600-M12Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required.

N5K-C5624Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required.

N5K-C5696Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required.

N5696-M12Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1a)	
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------------	--

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required

N5K-C56128P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	NX-OS 7.0(2)N1(1)
-------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- QSA (CVR-QSFP-SFP10G) required.

N56-M24UP2Q	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	NX-OS 7.0(2)N1(1)
-------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Notes for above line :

- QSFP Ports: QSA (CVR-QSFP-SFP10G) required.

N5K-C5548P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

N5K-C5548UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
-------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

N5K-C5596UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
-------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

N55-M16P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
----------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

N55-M16P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
----------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	-------------------

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N55-M8P8FP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N55-M8P8FP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N55-M16UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N5696-M20UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(4)N1(1)	

N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)

Network Device Notes for above line :

• QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.

N77-F324FQ-25	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
---------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

• QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required.

N77-M312CQ-26L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
----------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------	--------------

Network Device Notes for above line :

• QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.

N77-F248XP-23E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(2)	NX-OS 6.2(2)
N77-F348XP-23	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(6)	NX-OS 6.2(6)
N77-M348XP-23L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)DX(1)	NX-OS 7.3(0)DX(1)
N77-F430CQ-36	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)

Network Device Notes for above line :

• QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.

C8500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8500-12X4QC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-12X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500L-8S4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.4.1	IOS XE 17.4.1
C8500-20X6C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.4.1	IOS XE 17.10.1

C3850

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-48F	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	IOS XE 3.7.2
WS-C3850-48XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
WS-C3850-48T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-12S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-24S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-12XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-4-10G network module													
WS-C3850-12XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-16XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-32XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
C3850-NM-2-10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-4-10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-8-10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													

C6800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-32P10G-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)S

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
													Y
C6800-16P10G-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-8P10G-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-32P10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-16P10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-8P10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-SUP6T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.3(1)SY
C6800-SUP6T-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.3(1)SY
C6824-X-LE-40G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6840-X-LE-40G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6880-X-LE-16P10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6880-X-16P10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6816-X-LE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6832-X-LE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6800IA-48FPDR	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY3	IOS 15.1(2)SY3
C6880-X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6880-X-LE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1

C4500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X45-SUP9-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.10	IOS XE 3.10
WS-X4712-SFP+E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0SG	IOS 3.2.0SG
WS-X45-SUP7-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0SG	IOS 3.2.0SG
WS-X45-SUP7L-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0XO	IOS 3.2.0XO
WS-X45-SUP8-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0XO	IOS 3.0XO
WS-X45-SUP8L-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.8.1E	IOS 3.8.1E

FPRMID3

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR3K-XNM-8X25G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurati	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
												ons.	
3130	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3140	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR3K-XNM-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3105	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3110	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3120	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

C9200CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200CX-8P-2X2G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12P-2X2G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12T-2X2G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-8UXG-2X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4
C9200CX-8UXG-2XH	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4

IE9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-9320-22S2C4X-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-22S2C4X-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24T4X-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24T4X-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24P4X-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-24P4X-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-9320-16P8U4X-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed. 													
IE-9320-16P8U4X-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> • 10G uplink SFP+ fiber ports support 1Gb/s and 10Gb/s data rates. When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed. 													

FPRUHI

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-NM-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets , installation guides, and release notes for software configurations.	
FPR9K-SM-24	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets , installation guides, and release notes for software configurations.	
FPR9K-SM-36	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets , installation guides, and release notes for software configurations.	
FPR9K-SM-40	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets , installation guides, and release notes for software configurations.	
FPR9K-SM-44	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets , installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-SM-48	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR9K-SM-56	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

N3500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3524P-10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)A1(1)	NX-OS 5.0(3)A1(1)
N3K-C3548P-10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)A1(1)	NX-OS 5.0(3)A1(1)
N3K-C3524P-10GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(1)	NX-OS 6.0(2)A6(1)
N3K-C3548P-10GX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(1)	NX-OS 6.0(2)A6(1)
N3K-C3548P-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(3)	NX-OS 7.0(3)I7(3)
N3K-C3524P-XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(3)	NX-OS 7.0(3)I7(3)

C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9400-SUP-1XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-LC-24XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-SUP-1XL-Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
C9400-LC-48XS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
C9400-LC-24XY	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1
C9400-LC-12QC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1

Network Device Notes for above line :

- For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) required.

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSX-FI-6454-U	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCSX-FI-64108-U	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1
Network Device Notes for above line : • Uplink module for C9200-24P/48P/24T/48T													
C9200-NM-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
Network Device Notes for above line : • Uplink module for C9200-24PXG; C9200-48PXG													
C9200-NM-4X	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
Network Device Notes for above line : • Uplink module for C9200-48PL													
C9200-NM-2Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
Network Device Notes for above line : • Uplink module for C9200L-24PXG-4X/2Y; C9200L-48PXG-4X/2Y													

C3560CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560CX-12PD-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(3)E	IOS 15.2(3)E
WS-C3560CX-8XPD-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(3)E	IOS 15.2(3)E

CBR8

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CBR-SUP-8X10G-PIC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.18SP	
CBR-SUP-8X10G-PIC	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.7.1	IOS XE 16.7.1
CBR-DPIC-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.18SP	
CBR-DPIC-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.7.1	IOS XE 16.7.1

ESS3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ESS-3300-NCP-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
												software release information .	
ESS-3300-NCP-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

ME3800X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ME-3800X-24FS-M	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(52)EY	IOS 12.2(52)EY
Network Device Notes for above line : • SFP+ ports													

NCS6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-6008	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.0.0	IOS XR 5.0.0
NC6-60X10GE-LS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.1	IOS XR 5.2.1
NC6-60X10GE-MS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 5.2.1	IOS XR 5.2.1

FPRMID

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR2K-NM-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-2130	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-2140	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

C2960X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C2960X-HYBRID-STK	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
C2960X-HYBRID-STK	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.10.0E	IOS 3.10.0E
C2960X-FIBER-STK	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
C2960X-FIBER-STK	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.10.0E	IOS 3.10.0E
WS-C2960X-24TD-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-24PD-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-48TD-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-48LPD-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-48FPD-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX

C3560X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560X-24T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3560X-48T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3560X-24P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3560X-48P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3560X-48PF	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line :													
• With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													

C1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1000-24T-4X-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-24P-4X-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-24FP-4X-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-48T-4X-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-48P-4X-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-48FP-4X-L	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1

C9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9800-40-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-80-K9	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-10X10GE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-48YL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line :													
• When in use with C9600-SUP-1.													
C9600-LC-48YL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line :													
• When in use with C9600X-SUP-2.													
C9600-LC-24C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • When in use with C9600-SUP-1. QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9600-LC-24C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9600-LC-40YL4CD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. QSA (CVR-QSFP-SFP10G) supported from IOS XE 17.11.1 required for use in QSFP ports													
C9600-LC-40YL4CD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600X-LC-32CD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.11.1	IOS XE 17.11.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. For QSFP ports, QSA (CVR-QSFP-SFP10G) is required.													
C9600X-LC-56YL4C	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	IOS XE 17.13.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													

C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9400X-SUP-2XL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

C3750X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3750X-24T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-24P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48PF	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3750X-12S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3750X-24S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SE	IOS 15.0(2)SE
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													

N6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N6K-C6001-64P	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(1)	
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> For QSFP Ports: QSA (CVR-QSFP-SFP10G) required. 													
N6K-C6001-64T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)N2(1)	
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> For QSFP Ports: QSA (CVR-QSFP-SFP10G) required. 													
N6004X-M20UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(1)N1(1)	

FPRLOW

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-1150	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
<p>Network Device Notes for above line :</p> <ul style="list-style-type: none"> Two of the SFP ports (ports 9 and 11) support 10 Gb/s data rate. 													

N2000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N2K-C2248PQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see device release notes/data sheet for min SW releases	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
												as SW is dependent on host platform.	
N2K-C2348TQ-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	

Network Device Notes for above line :

• Uplink QSFP ports with QSA (CVR-QSFP-SFP10G) adapter

N2K-C2148T	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2248TP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2232PP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2224TP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2232TM	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2232TM-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.2(1)N1(1a)	NX-OS 5.2(1)N1(1a)
N2K-C2348TQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1)	

Network Device Notes for above line :

• Uplink QSFP ports with QSA (CVR-QSFP-SFP10G) adapter

N2K-C2248TP-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2248TP-E	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
N2K-C2348UPQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(4)N1(1)	NX-OS 7.0(4)N1(1)

Network Device Notes for above line :

• For QSFP Ports, QSA (CVR-QSFP-SFP10G) required.

N2K-C2348UPQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
--------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	--------------------	--------------------

Network Device Notes for above line :

• For QSFP Ports, QSA (CVR-QSFP-SFP10G) required.

N2K-C2332TQ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	
-------------	------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	-------------------	--

Network Device Notes for above line :

• Uplink QSFP ports with QSA (CVR-QSFP-SFP10G) adapter

C9300LM

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300LM-24U-4Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48U-4Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48UX-4Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48T-4Y	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1

ASR920

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-920-10SZ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13
ASR-920-12CZ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13
ASR-920-12SZ-IM	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-920-24SZ-M	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-24SZ-IM	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-4SZ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13
ASR-920-24TZ-M	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.14	IOS XE 3.14
ASR-920-12SZ	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
ASR-920-20SZ-M	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR-920-10SZ-PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13
ASR-920-8S4Z-PD	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.13	IOS XE 3.13

FPRHIGH

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR4K-NM-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4110	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4120	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4140	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4150	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-4112	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-4115	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-4125	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-4145	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR4K-XNM-8X10G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR4K-XNM-8X25G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

C2960L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960L-24TQ-LL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
WS-C2960L-24PQ-LL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
WS-C2960L-48TQ-LL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
WS-C2960L-48PQ-LL	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E

UCSB

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCS-FI-6454	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108-U	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-6454-U	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NC55-36X100G	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-24X100G-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-24H12F-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-36X100G-A-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-5501	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5501-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-5502-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-36H-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NCS-55A1-24H	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-36H-SE-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NC55-MOD-A-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-12T-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MOD-A-SE-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A2-MOD-HD-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-SE-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A2-MOD-HX-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-SE-H-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A1-48Q6H	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NCS-55A1-24Q6H-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-55A1-24Q6H-SS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-32T16Q4H-A	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.2	IOS XR 7.2.2
NC57-36H-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57B1-6D24H-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57B1-5D24-SE	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57C3-MOD-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NCS-57C3-MOD-SE-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NC57-36H6D-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC57-MOD-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NCS-57C1-48Q6-SYS	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
NC57-MPA-12L-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NC55-OIP-02	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.7.1	IOS XR 7.7.1
Network Device Notes for above line : • Supported on NCS-57C3 and NCS-55A2													
NC57-48Q2D-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NC57-48Q2D-SE-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NCS-57C1-48Q6D-S	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2