

Cisco SFP-10G-LR-S Compatibilty Matrix Datasheet



Click here to buy this
transceiver

[BUY NOW](#)

C2960X
C2960XR
C9400
C9500
N3500
N2000
N5000
N7000
UCSB
UCSC
NCS5500
FPRHIGH
FPRUHI
C2960L
C3560CX
C6500
C6800
C2360
OS
N4000
FPRMID
C4900
C4900M
N9300
N3000
C9300
N9500
N9200
ASR9000
C6000
ASR1000
ASR903
ASR920

C2960X
NCS4200
C3750
C4500
C4500X
C3850
C3750X
C3650
C3560
C3560X
NCS540
NCS560
AIRCT12
C9200
C9200L
C9600
C9300L
N9800
C9800
IE3300
N7700
350 Series
C1000
Intel
Qlogic
250 Series
550 Series
CBS350 Series
CBS250 Series
NCS520
8000 Series
C8500
C8300
CGPON
C9300X
UCSX
N3550
C9400X

C2960X
 C9200CX
 C9300LM
 CBS220 Series
 C1300
 FPRLOW
 CSF4200
 FPRMID3
 ESS3300

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required.													
C9300L-24T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24UXG-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-2Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required.													
C9300L-48PF-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2

ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-4T16GE-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
A9K-4T16GE-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
A9K-24X10GE-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.3	IOS XR 6.1.3
A9K-24X10GE-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.3	IOS XR 6.1.3
A9K-MPA-8X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD400													
A9K-MPA-8X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
Network Device Notes for above line : • On MOD200													
A9K-MPA-8X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-MPA-8X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-24X10GE-1G-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.1	IOS XR 64 Bit 6.2.1
A9K-24X10GE-1G-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-24X10GE-1G-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.1	IOS XR 64 Bit 6.2.1
A9K-24X10GE-1G-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-48X10GE-1G-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.1	IOS XR 64 Bit 6.2.1
A9K-48X10GE-1G-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-48X10GE-1G-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.1	IOS XR 64 Bit 6.2.1
A9K-48X10GE-1G-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-MPA-20X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200													
A9K-MPA-20X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200													
A99-48X10GE-1G-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
A99-48X10GE-1G-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
ASR-9901	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9K-4HG-FLEX-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A9K-4HG-FLEX-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-TR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
ASR-9902	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.10.1	IOS XR 64 Bit 7.10.1
Network Device Notes for above line : • Maximum number of SFP-10G-LR-S supported is 40.													
ASR-9902-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.10.1	IOS XR 64 Bit 7.10.1
Network Device Notes for above line : • Maximum number of SFP-10G-LR-S supported is 40.													
A9K-4HG-FLEX-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-4HG-FLEX-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.4.1	IOS XR 64 Bit 7.4.1
A99-48X10GE-1G-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
A99-48X10GE-1G-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.2	IOS XR 6.5.2
A9K-24X10GE-1G-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.1	IOS XR 64 bit 6.2.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-24X10GE-1G-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-MPA-8X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD400													
A9K-MPA-8X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.2	IOS XR 64 bit 6.3.2
Network Device Notes for above line : • On MOD200													
A9K-MPA-8X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-8X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-20X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD200													
A9K-MPA-20X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-8X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD200													
ASR-9901-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 7.0.1	IOS XR 64 Bit 7.0.1
A9K-48X10GE-1G-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.1	IOS XR 64 bit 6.2.1
A9K-48X10GE-1G-FC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1

CSF4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-4215	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4225	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-4245	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M132XP-12	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.0 (3)	NX-OS 4.0 (3)
N7K-M108X2-12L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.2(3a)	NX-OS 5.2(3a)

Network Device Notes for above line :

- With OneX converter

N7K-M132XP-12L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1	NX-OS 5.1
N7K-M224XP-23L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(1)	NX-OS 6.1(1)
N7K-F312FQ-25	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)

Network Device Notes for above line :

- QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required.

N7K-F132XP-15	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1	NX-OS 5.1
N7K-F248XP-25	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(1)	NX-OS 6.0(1)
N7K-F248XP-25E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)	NX-OS 6.1(2)
N7K-F348XP-25	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(12)	NX-OS 6.2(12)
N7K-M348XP-25L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)
N7K-M324FQ-25L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)

Network Device Notes for above line :

- QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540-ACC-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-ACC-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
N540X-16Z4G8Q2C-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-16Z4G8Q2C-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-28Z4C-SYS-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-28Z4C-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-12Z16G-SYS-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540X-12Z16G-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-12Z20G-SYS-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1
N540-12Z20G-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.0.1	IOS XR 7.0.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540X-8Z16G-SYS-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-8Z16G-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-6Z18G-SYS-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-6Z18G-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540-FH-CSR-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N540X-4Z14G2Q-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540X-4Z14G2Q-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-24Q8L2DD-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540-FH-AGG-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
N540-6Z18G-SYS-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
N540-6Z18G-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
N540-6Z14S-SYS-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
N540X-16Z8Q2C-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3232C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N3K-C36180YCR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N3K-C3064PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)U1(1a)	NX-OS 5.0(3)U1(1a)
N3K-C3064PQ-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)U1(2)	NX-OS 5.0(3)U1(2)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3064PQ-10GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3064PQ-10GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	—
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-40GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • SFP Port													
N3K-C3132Q-40GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
N3K-C3132Q-40GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3132Q-40GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • For native SFP+ ports and with CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3132Q-V	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • For native SFP+ ports and with CVR-QSFP-SFP10G adapter (QSA).													
N3K-C3172TQ-10GT	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Port: QSA (CVR-QSFP-SFP10G) required.													
N3K-C3172TQ-32T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Port: QSA (CVR-QSFP-SFP10G) required.													
N3K-C3172PQ-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • For QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N3K-C3172PQ-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
Network Device Notes for above line : • For QSFP Ports: CVR-QSFP-SFP10G adapter (QSA) is required.													
N3K-C3172TQ-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
Network Device Notes for above line : • With CVR-QSFP-SFP10G adapter (QSA).													
N3K-C31108PC-V	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
N3K-C31108TC-V	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N3K-C31128PQ-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3264Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3048TP-1GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
N3K-C3264C-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
Network Device Notes for above line : • For QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required.													
N3K-C3132C-Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)
Network Device Notes for above line : • For QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required.													
N3K-C34180YC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.2	—
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N3K-C34200YC-SM	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2V)	NX-OS 9.2(2V)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4900M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
ME-4924-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													

C3750

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3750E-24TD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE1	IOS 12.2(55)SE1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3750E-24PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE1	IOS 12.2(55)SE1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3750E-48TD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE1	IOS 12.2(55)SE1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3750E-48PDF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE1	IOS 12.2(55)SE1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													

IE3300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
IE-3300-8T2X-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8T2X-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
Network Device Notes for above line : • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8U2X-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.													
IE-3300-8U2X-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

Network Device Notes for above line :
• When using nonindustrial rated transceivers, the hardened platform operating temperature range is de-rated. Please refer to the Cisco IE Datasheet or Hardware Installation Guide to calculate switch operating temperature ranges when nonindustrial SFPs are deployed.

C6500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X6716-10G-3C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(33)SX J1	IOS 12.2(33) SXJ1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-X6716-10G-3CXL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(33)SX J1	IOS 12.2(33) SXJ1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-X6708-10G-3C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(33)SX J1	IOS 12.2(33) SXJ1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-X6708-10G-3CXL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(33)SX J1	IOS 12.2(33) SXJ1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
VS-S720-10G-3C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(33)SX J1	IOS 12.2(33) SXJ1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
VS-S720-10G-3CXL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(33)SX J1	IOS 12.2(33) SXJ1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	NX-OS 70314.2
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required, Min SW Release ACI-N9KDK9-12.1(1).													
N9K-C93180YC-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YCFX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required. ___ c) QSP Ports (49 - 52) supports 40G breakout, Min SW Release ACI-N9KDK9-13.2(1).													
N9K-C9348GCFXP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	NX-OS 70317.1
Network Device Notes for above line : • Supported on ports 49 - 52 only													
N9K-C9348GCFXP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) SFP Ports (49-52). ___ b) QSFP Ports (53-54), QSA (CVR-QSFP-SFP10G) required, Min SW Release ACI-N9KDK9-13.1(2).													
N9K-C93240YCFX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.3	NX-OS 70317.3
Network Device Notes for above line : • SFP Ports (1-48). Breakout not supported.													
N9K-C93240YCFX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-60), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336CFX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1(2)	ACI-N9KDK9-13.1(2)
Network Device Notes for above line : • a) QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required. ___ b) QSFP Ports (1-30), 40G breakout supported.													
N9K-C9336CFX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.03.17.3	NX-OS 7.03.17.3
Network Device Notes for above line : • QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336CFX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(3)F	NX-OS 10.3(3)F
Network Device Notes for above line : • QSFP Ports (1-36), QSA28 (CVR-QSFP28-SFP25G) required.													
N9K-M12PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)11(2)	NX-OS 7.0(3)11(2)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-M6PQE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)12(1)	NX-OS 7.0(3)12(1)
N9K-C9372PX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)13(1)	NX-OS 6.1(2)13(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9372PX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C9372PXE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)12(1)	NX-OS 7.0(3)12(1)
Network Device Notes for above line : • a) SFP Ports (1-48). ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9372PXE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48)													
N9K-C9332PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)11(2)	NX-OS 7.0(3)11(2)
Network Device Notes for above line : • QSFP Ports (27-32): QSA (CVR-QSFP-SFP10G) required													
N9K-C9332PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.0	ACI-N9KDK9-12.0
Network Device Notes for above line : • QSFP Ports (1-26): QSA (CVR-QSFP-SFP10G) required													
N9K-C93120TX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)11(2)	NX-OS 7.0(3)11(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C9372TX-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3(1)	NX-OS 7.0(3)I3(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-C93108TC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.0(1)	ACI-N9KDK9-12.0(1)
Network Device Notes for above line : • QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required, min SW Release ACI-N9KDK9-12.1(1).													
N9K-C93108TC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 703i5.1	NX-OS 703i5.1
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180LC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180LC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 703i7.1	
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required. Mode 1: 28 x 40G + 4 x 40G/100G (If top port is configured as 10G or 1G using QSA adapter; the bottom port also needs to be 10G or 1G to match the speed). Mode 2: 24 x 40G + 6 x 40G/100G (If top port is configured as 10G or 1G using QSA adapter; the bottom port also needs to be 10G or 1G to match the speed). Port 26 and 28 are disabled. Mode 3: 18 x 40G/100G (QSA is supported on all the 18 ports.)													
N9K-C93108TC-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2A	ACI-N9KDK9-12.2A
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TC-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 703i7.1	NX-OS 703i7.1
Network Device Notes for above line : • QSFP Ports (49-54): QSA (CVR-QSFP-SFP10G) required.													
N9K-C9364C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • a) QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required. b) SFP Ports (65-66).													
N9K-C9364C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.1	NX-OS 9.2.1
Network Device Notes for above line : • a) QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required. b) SFP Ports (65-66).													
N9K-C9396PX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(1)	NX-OS 6.1(2)I2(1)
N9K-C9396PX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0	ACI-N9KDK9-13.0(1)
N9K-C9332C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • a) QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required. b) SFP Ports (33-34).													
N9K-C9332C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)
Network Device Notes for above line : • a) QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required. b) SFP Ports (33-34).													
N9K-C93360YC-FX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
Network Device Notes for above line : • a) SFP Ports (1-96). b) QSFP Ports (97-108), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93360YC-FX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
Network Device Notes for above line : • SFP Ports (1-96). QSFP Ports (97-108): QSA (CVR-QSFP-SFP10G) required.													
N9K-C93216TC-FX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
Network Device Notes for above line : • QSFP Ports (97-108), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93216TC-FX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
Network Device Notes for above line : • QSFP Ports (97-108), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93216TC-FX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
Network Device Notes for above line : • QSFP Ports (97-108), QSA28 (CVR-QSFP28-SFP25G) is required													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93600CD-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C93600CD-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9316D-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(2)	ACI-N9KDK9-14.2(2)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9316D-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364C-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364C-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3I)	ACI-N9KDK9-14.2(3I)
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C93180YC-FX3S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested. ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested. ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested for ACI-N9KDK9-15.2.x onwards. ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested. ___ b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336C-FX2-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1.1	NX-OS 10.1.1
Network Device Notes for above line : • QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required.													
N9K-C9336C-FX2-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(4)	ACI-N9KDK9-15.2(4)
Network Device Notes for above line : • a) QSFP Ports (1-36), QSA (CVR-QSFP-SFP10G) required. ___ b) QSFP Ports (1-30), 40G breakout supported.													
N9K-C93108TC-FX3P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TC-FX3P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C9332D-GX2B	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(3)	ACI-N9KDK9-15.2(3)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9332D-GX2B	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.2(1q) F	NX-OS 10.2(1q) F
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9348D-GX2A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9348D-GX2A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364D-GX2A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.2(5)	ACI-N9KDK9-15.2(5)
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9364D-GX2A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.2(3) F	NX-OS 10.2(3) F
Network Device Notes for above line : • For QSFP-DD ports, QSA (CVR-QSFP-SFP10G) required													
N9K-C9332D-H2R	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
Network Device Notes for above line : • For QDD ports, QSA (CVR-QSFP-SFP10G) or QSA28 (CVR-QSFP28-SFP25G) required													
N9K-C9348GC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C9348GC-FX3PH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C93108TC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) or QSA (CVR-QSFP-SFP10G) is required													
N9K-C93108TC-FX3	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) or QSA (CVR-QSFP-SFP10G) is required													
N9K-C93400LD-H1	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F

ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR1001-X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
ASR1002-HX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1001-HX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
EPA-10X10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1

Intel

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Intel X710	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	—	—
Intel XXV710	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	—	—

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X97160YC-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • 1) SFP ports (1-48) 2) QSFP ports (49-52), QSA (CVR-QSFP-SFP10G) required.													
N9K-X9564PX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I1(1)	NX-OS 6.1(2)I1(1)
Network Device Notes for above line : • Downlinks.													
N9K-X9464PX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I2(2a)	NX-OS 6.1(2)I2(2a)
N9K-X9432PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(1)	NX-OS 7.0(3)I5(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-X9464TX2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7034.1	NX-OS 7034.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-X9732C-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9732C-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(2)	NX-OS 7.0(3)I7(2)
Network Device Notes for above line : • QSFP Ports (1-36): QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.1	ACI-N9KDK9-13.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736C-EX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I6(1)	NX-OS 7.0(3)I6(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9788TC-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.03.17.3	NX-OS 7.03.17.3
Network Device Notes for above line : • QSFP Ports (49-52): QSA (CVR-QSFP-SFP10G) required													
N9K-X9732C-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X96136YC-R	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
N9K-X9736Q-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0.3I7.6	NX-OS 7.0.3I7.6
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9736Q-FX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(1)	ACI-N9KDK9-14.1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-X9716D-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-X9716D-GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(1)	ACI-N9KDK9-15.1(1)
Network Device Notes for above line : • QSFP-DD Ports, QSA (CVR-QSFP-SFP10G) required.													
N9K-X9400-8D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • Please see release note or configuration guide for 10G with QSA consideration													
N9K-X9400-16W	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Network Device Notes for above line : • For QSFP56 ports, QSA (CVR-QSFP-SFP10G) required													
N9K-X9400-16W	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
Network Device Notes for above line : • Please see release note or configuration guide for 10G with QSA consideration													

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-12Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-2C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. QSA28 (CVR-QSFP28-SFP25G) can also be used from IOS XE 17.12.1. Uplink module for C9300X models only													
C9300X-24Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-8Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-4C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. QSA28 (CVR-QSFP28-SFP25G) can also be used from IOS XE 17.12.1. Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y.													

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-24													
C9500-24Y4C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-24; QSFP Ports 25-28: QSA (CVR-QSFP-SFP10G) required.													
C9500-48Y4C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-48													
C9500-48Y4C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-48; QSFP Ports 49-52: QSA (CVR-QSFP-SFP10G) required.													
C9500-12Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-24Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1a	IOS XE 16.5.1a
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-40X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-NM-2Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-32QC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-32C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-NM-8X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-16X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500X-28C8D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													
C9500X-60L4D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN													
C9300-NM-8X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1
C9300-NM-2Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN													

C3560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560E-24TD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	IOS 12.2(55)SE 1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3560E-24PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	IOS 12.2(55)SE 1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3560E-48TD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	IOS 12.2(55)SE 1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3560E-48PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	IOS 12.2(55)SE 1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3560E-48PDF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	IOS 12.2(55)SE 1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3560E-12SD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE1	IOS 12.2(55)SE1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C3560E-12D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE1	IOS 12.2(55)SE1
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													

NCS4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4200-1T8LR-PS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
NCS4201-SA	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
NCS 4201-SA	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	
NCS4200-8T-PS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
NCS4202-SA	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17

CGPON

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CGP-OLT-8T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	1.2.1.17	1.2.1.17
CGP-OLT-16T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	1.2.1.17	1.2.1.17

ESS3300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ESS-3300-NCP-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	
ESS-3300-NCP-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and release notes for minimum software release information .	

C4500X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4500X-32SFP+	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-F-32SFP+	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-F-32SFP+	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
C4KX-NM-8SFP+	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-16SFP+	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG
WS-C4500X-F-16SFP+	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG
WS-C4500X-24X-ES	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG

C1300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1300-8T-E-2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-8P-E-2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-8FP-2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-16T-2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-16P-2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-16FP-2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1300-24T-4G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-24P-4G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-24FP-4G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-48T-4G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-48P-4G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-16P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-24T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-24P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-24FP-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1300-48T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1300-48P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

250 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
SG250X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.3.5.63	2.3.5.63

N3550

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N35-T-48X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1(2T)	NX-OS 10.1(2T)

N4000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N4K-4001I-XPX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.1(2)E1(1)	NX-OS 4.1(2)E1(1)

C2960XR

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960XR-24TD-I	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-48TD-I	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-24PD-I	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-48LPD-I	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1
WS-C2960XR-48FPD-I	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX1	IOS 15.0(2)EX1

C6000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X6908-10G-2T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-X6908-10G-2TXL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-X6904-40G-2T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • With CVR-CFP-4SFP10G FourX converter for CFP ports													
WS-X6904-40G-2TXL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • With CVR-CFP-4SFP10G FourX converter for CFP ports													
VS-S2T-10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
VS-S2T-10G-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													

C8300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8300-2N2S-4T2X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
C8300-1N1S-4T2X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
C-NIM-1X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
C-NIM-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.11.1	IOS XE 17.11.1

8000 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
8201	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8202	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8800-LC-36FH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
8800-LC-48H	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8201-32FH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
88-LC0-36FH-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
88-LC0-36FH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.15	IOS XR 7.3.15
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8101-32FH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8101-32H	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
88-LC0-34H14FH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.3	IOS XR 7.3.3
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8202-32FH-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
8201-24H8FH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
86-MPA-14H2FH-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
86-MPA-4FH-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
Network Device Notes for above line : • For QSFP Port, QSA (CVR-QSFP-SFP10G) required.													
86-MPA-24Z-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1

C2360

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
2360-48TD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)EY	—

CBS250 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CBS250	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	3.0.0.61	3.0.0.61

ASR903

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA8S1Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
A900-IMA8T1Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
A900-IMA2Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
A900-IMA8Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	

C9200L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200L-24P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PXG-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-2Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PXG-2Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PL-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1

C4900

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4948-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)S G	IOS 12.2(54)S G
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C4928-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)S G	IOS 12.2(54)S G
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C4948E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)S G	IOS 12.2(54)S G

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X4904-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)S G	IOS 12.2(54)SG
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-X4908-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)S G	IOS 12.2(54)SG
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-C4948E-F	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)S G	IOS 12.2(54)SG

NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA-8Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
A900-IMA-8Z-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N560-IMA-8Q/4L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	NX-OS 7.0(3)I3.1
N9K-C92160YC-X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70315.1	NX-OS 70315.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-C92300YC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70316.1	NX-OS 70316.1
N9K-C9236C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70315.1	
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N9K-C9272Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.03(I)5.1	NX-OS 7.03(I)5.1
Network Device Notes for above line : • QSFP Port: QSA (CVR-QSFP-SFP10G) required. Supported on ports 37-71.													
N9K-C92348GC-X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
Network Device Notes for above line : • For QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													

CBS220 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CBS220	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.0.0.17	2.0.0.17

NCS520

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N520-4G4Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
N520-X-4G4Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
N520-20G4Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
N520-X-20G4Z	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1

N9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9836DM-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(1)	NX-OS 10.3(1)

Network Device Notes for above line :

- For QSFP-DD Ports (1-36), QSA (CVR-QSFP-SFP10G) required

C3650

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-12X48UZ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-24TD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48TD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-24PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-24PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-24PDM	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48FD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48TQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48TQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-8X24PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
WS-C3650-8X24UQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-12X48UQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-12X48UR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48FQM	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE
WS-C3650-48FQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.0SE	IOS XE 3.3.0SE

N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N5K-C5672UP-	SFP-10G-LR-S	TMG	10	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to	Y	NX-OS	NX-OS

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
16G			Gbps					UPC)		70C		7.0(1)N1(1)	7.0(1)N1(1)
N5K-C5672UP-16G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	
Network Device Notes for above line : • QSA Ports: QSA (CVR-QSFP-SFP10G) is required.													
N5K-C5672UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(1)N1(1)	NX-OS 7.0(1)N1(1)
Network Device Notes for above line : • For QSFP Ports: QSA (CVR-QSFP-SFP10G) is required													
N5K-C5648Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
N5600-M12Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N5K-C5624Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N5K-C5696Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	NX-OS 7.1(1)N1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N5K-C56128P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	NX-OS 7.0(2)N1(1)
Network Device Notes for above line : • QSA (CVR-QSFP-SFP10G) required.													
N56-M24UP2Q	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(2)N1(1)	NX-OS 7.0(2)N1(1)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N5K-M1600	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.0(1a)N1(1)	NX-OS 4.0(1a)N1(1)
N5K-M1404	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.0(1a)N1(1)	NX-OS 4.0(1a)N1(1)
N5K-C5548P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(2)N1(1)	NX-OS 5.0(2)N1(1)
N5K-C5548UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
N5K-C5596UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
N5K-C5010P-BF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.0(1a)N1(1)	NX-OS 4.0(1a)N1(1)
N5K-C5020P-BF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.0(1a)N1(1)	NX-OS 4.0(1a)N1(1)
N55-M16P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(2)N1(1)	NX-OS 5.0(2)N1(1)
N55-M16P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
N55-M8P8FP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(2)N1(1)	NX-OS 5.0(2)N1(1)
N55-M8P8FP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
N55-M16UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													
N77-F324FQ-25	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required.													
N77-M312CQ-26L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													
N77-F248XP-23E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(2)	NX-OS 6.2(2)
N77-F348XP-23	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(6)	NX-OS 6.2(6)
N77-M348XP-23L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)
N77-F430CQ-36	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													

C8500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8500-12X4QC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-12X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500L-8S4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.4.1	IOS XE 17.4.1
C8500-20X6C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.4.1	IOS XE 17.10.1

C3850

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-48F	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	IOS XE 3.7.2
WS-C3850-48XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required.													
WS-C3850-48T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-24T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.2.0SE	IOS XE 3.2.0SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-12S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-24S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-12XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-4-10G network module													
WS-C3850-12XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-16XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-32XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
C3850-NM-2-10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-4-10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-8-10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													

C6800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-32P10G-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-16P10G-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-8P10G-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-32P10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-16P10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-8P10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-SUP6T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.3(1)SY
C6800-SUP6T-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.3(1)SY
C6880-X-LE-16P10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6880-X-16P10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6832-X-LE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)SY	IOS 15.2(2)SY
C6800IA-48FPDR	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY3	IOS 15.1(2)SY3
C6880-X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6880-X-LE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1

C4500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X4606-X2-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG

Network Device Notes for above line :

- With CVR-X2-SFP10G converter for X2 ports

WS-X45-SUP9-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.10	IOS XE 3.10
WS-X4013+10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG

Network Device Notes for above line :

- With CVR-X2-SFP10G converter for X2 ports

WS-X4516-10GE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG
---------------	--------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	----------------	----------------

Network Device Notes for above line :

- With CVR-X2-SFP10G converter for X2 ports

WS-X45-SUP6-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG
---------------	--------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	----------------	----------------

Network Device Notes for above line :

- With CVR-X2-SFP10G converter for X2 ports

WS-X45-SUP6L-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(54)SG	IOS 12.2(54)SG
WS-X4712-SFP+E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1.0SG	IOS 3.1.0SG
WS-X45-SUP7-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1.0SG	IOS 3.1.0SG
WS-X45-SUP7L-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0XO	IOS 3.2.0XO
WS-X45-SUP8-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0XO	IOS 3.0XO
WS-X45-SUP8L-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.8.1E	IOS 3.8.1E

FPRMID3

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR3K-XNM-8X25G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
3130	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3140	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR3K-XNM-8X10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3105	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3110	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3120	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

CBS350 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
CBS350	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	3.0.0.61	3.0.0.61

C9200CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200CX-8P-2X2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12P-2X2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12T-2X2G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-8UXG-2X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4
C9200CX-8UXG-2XH	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4

AIRCT12

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
AIR-CT5520	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	8.1	

FPRUHI

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-NM-8X10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-24	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-36	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-40	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-44	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-SM-48	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR9K-SM-56	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

N3500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3524P-10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3548P-10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3524P-10GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3548P-10GX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3548P-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(3)	NX-OS 7.0(3)I7(3)
N3K-C3524P-XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(3)	NX-OS 7.0(3)I7(3)

C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9400-SUP-1XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-LC-24XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-SUP-1XL-Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
C9400-LC-48XS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
C9400-LC-24XY	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1
C9400-LC-12QC	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1

Network Device Notes for above line :

- For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) required.

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSX-FI-6536	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.2	UCS Manager v4.2(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
UCSX-FI-6536-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.2	UCS Manager v4.2(2)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
UCS-FI-6536	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	UCS Manager v4.2(3)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
UCSX-FI-6454-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCSX-FI-64108-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1
Network Device Notes for above line : • Uplink module for C9200-24P/48P/24T/48T													
C9200-NM-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
Network Device Notes for above line : • Uplink module for C9200-24PXG; C9200-48PXG													
C9200-NM-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
Network Device Notes for above line : • Uplink module for C9200-48PL													
C9200-NM-2Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
Network Device Notes for above line : • Uplink module for C9200L-24PXG-4X/2Y; C9200L-48PXG-4X/2Y													

C3560CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560CX-12PD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(4)E2	IOS 15.2(4)E2
WS-C3560CX-8XPD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(4)E2	IOS 15.2(4)E2

350 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
SG350X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.3.5.63	2.3.5.63
SG350XG	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.3.5.63	2.3.5.63
SX350X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.4.0.94	2.4.0.94

FPRMID

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR2K-NM-8X10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-2130	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-2140	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

550 Series

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
SF550X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.3.5.63	2.3.5.63
SG550X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.3.5.63	2.3.5.63
SG550XG	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.3.5.63	2.3.5.63
SX550X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	2.4.0.94	2.4.0.94

C2960X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C2960X-HYBRID-STK	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
C2960X-HYBRID-STK	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.10.0E	IOS 3.10.0E
C2960X-FIBER-STK	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
C2960X-FIBER-STK	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.10.0E	IOS 3.10.0E
WS-C2960X-24TD-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-24PD-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-48TD-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960X-48LPD-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX
WS-C2960X-48FPD-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)EX	IOS 15.0(2)EX

OS

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-CBS3120X-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	—
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-CBS3130X-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	—
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													
WS-CBS3110X-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE 1	—
Network Device Notes for above line : • With CVR-X2-SFP10G converter for X2 ports													

C3560X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560X-24T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-48T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-24P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-48P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-48PF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													

C1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1000-24T-4X-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-24P-4X-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-24FP-4X-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-48T-4X-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-48P-4X-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1
C1000-48FP-4X-L	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(7)E1	IOS 15.2(7)E1

C9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9800-40-K9	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-L-F-K9	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	
C9800-80-K9	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see release notes for minimum software release information .	

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-SUP-1	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • Only for SFP+ Mgmt Port on Supervisor													
C9600-LC-48YL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600-LC-48YL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-24C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1. QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9600-LC-24C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • When in use with C9600X-SUP-2. QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9600X-SUP-2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • Only for SFP+ Mgmt Port on Supervisor													
C9600-LC-40YL4CD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. QSA (CVR-QSFP-SFP10G) supported from IOS XE 17.11.1 required for use in QSFP ports													
C9600-LC-40YL4CD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600X-LC-32CD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.11.1	IOS XE 17.11.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. For QSFP ports, QSA (CVR-QSFP-SFP10G) is required.													
C9600X-LC-56YL4C	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	IOS XE 17.13.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													

C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9400X-SUP-2XL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

C3750X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3750X-24T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-24P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48P	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48PF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(53)SE	IOS 12.2(53)SE

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3750X-12S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE5	IOS 12.2(55)SE5
Network Device Notes for above line : <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													
WS-C3750X-24S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 12.2(55)SE5	IOS 12.2(55)SE5
Network Device Notes for above line : <ul style="list-style-type: none"> With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules) 													

FPRLOW

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-1150	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
Network Device Notes for above line : <ul style="list-style-type: none"> Two of the SFP ports (ports 9 and 11) support 10 Gb/s data rate. 													

N2000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N2K-C2248PQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see device release notes/data sheet for min SW releases as SW is dependent on host platform.	
N2K-C2348TQ-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(0)N1(1)	
Network Device Notes for above line : <ul style="list-style-type: none"> Uplink QSFP ports with QSA (CVR-QSFP-SFP10G) adapter 													
N2K-C2148T	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.0(1a)N2(1)	NX-OS 4.0(1a)N2(1)
N2K-C2248TP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2232PP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2224TP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 4.2(1)N2(1)	NX-OS 4.2(1)N2(1)
N2K-C2232TM	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N2(1)	NX-OS 5.0(3)N2(1)
N2K-C2232TM-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.2(1)N1(1a)	NX-OS 5.2(1)N1(1a)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N2K-C2348TQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(0)N1(1)	
Network Device Notes for above line : • Uplink QSFP ports with QSA (CVR-QSFP-SFP10G) adapter													
N2K-C2248TP-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N2K-C2248TP-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
N2K-C2348UPQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)N1(1)	NX-OS 7.0(3)N1(1)
N2K-C2348UPQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
N2K-C2332TQ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.1(1)N1(1)	
Network Device Notes for above line : • Uplink QSFP ports with QSA (CVR-QSFP-SFP10G) adapter													

Qlogic

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Qlogic QLE41212HLCU	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	—	—

C9300LM

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300LM-24U-4Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48U-4Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48U-4Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48T-4Y	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1

ASR920

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-920-10SZ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-12CZ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-12SZ-IM	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-24SZ-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-24SZ-IM	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-4SZ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-24TZ-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-12SZ	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
ASR-920-20SZ-M	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR-920-10SZ-PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-8S4Z-PD	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17

FPRHIGH

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR4K-NM-8X10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4110	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4120	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4140	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4150	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4112	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR-4115	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-4125	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-4145	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR4K-XNM-8X10G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR4K-XNM-8X25G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

C2960L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960L-24TQ-LL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
WS-C2960L-24PQ-LL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
WS-C2960L-48TQ-LL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
WS-C2960L-48PQ-LL	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E

UCSC

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSC-PCIE-C25Q-04	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0	—
Network Device Notes for above line : • VIC 1455													
UCSC-MLOM-C25Q-04	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0	—
Network Device Notes for above line : • VIC 1457													
UCSC-PCIE-ID10GF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS HUU 4.0(1c)	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • General Product ID: Intel X710. Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-PCIE-IQ10GF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS HUU 4.0(1c)	—
Network Device Notes for above line : • Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-PCIE-QD25GF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS HUU 4.0(1c)	—
Network Device Notes for above line : • General Product ID: Qlogic QLE41212HLCU. Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-PCIE-ID25GF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS HUU 4.0(1c)	—
Network Device Notes for above line : • Operating System: CentOS Linux 7.5.1804; NIC firmware Driver Version I40e / 2.1.14-k													
UCSC-P-M4D25GF	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS HUU 4.1(1f)	—
UCSC-M-V25-04	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.1	—
Network Device Notes for above line : • VIC 1467. For 6300 and 6400 server fabric interconnect.													
UCSC-M-V5Q50G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	—
Network Device Notes for above line : • VIC 15428. 10G connectivity from VIC 15428 is supported with UCS fabric interconnect 6300/6400 series and standalone switches. UCS-FI-6536 does not currently support 10-Gbps connectivity to UCS VIC 15428.													
UCSC-M-V5Q50G-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	—
Network Device Notes for above line : • VIC 15428. 10G connectivity from VIC 15428 is supported with UCS fabric interconnect 6300/6400 series and standalone switches. UCS-FI-6536 does not currently support 10-Gbps connectivity to UCS VIC 15428.													
UCSC-P-V5Q50G-D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.3.1	—
Network Device Notes for above line : • VIC 15425													
UCSC-P-V5Q50G	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.2.3	—
Network Device Notes for above line : • VIC 15425													
UCSC-M-V5Q50GV2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	—
Network Device Notes for above line : • VIC 15427													
UCSC-M-V5Q50GV2D	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.3(2c)	—
Network Device Notes for above line : • VIC 15427													

UCSB

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCS-FI-6296UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v2.0(1)	UCS Manager v2.0(1)
UCS-FI-M-6324	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v3.1(1e)	UCS Manager v3.1(1e)
UCS-FI-6332-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v3.1	UCS Manager v3.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
UCS-FI-6332-16UP-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v3.0	UCS Manager v3.0
UCS-FI-6332-16UP-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v3.1	UCS Manager v3.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required													
UCSB-5108-AC2	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v2.0(1)	—
UCS-IOM-2204XP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v2.0(1)	—
UCS-FI-6248UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v2.0(1)	UCS Manager v2.0(1)
UCS-FI-E16UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v2.0(1)	UCS Manager v2.0(1)
UCS-IOM-2208XP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v2.0(1)	—
UCS-FI-6454	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-6454-U	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS-5501	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5501-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
NCS-5502	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-36H-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-24H	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-36X100G-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
NCS-55A1-36H-SE-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-MOD-A-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MPA-12T-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC55-MOD-A-SE-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A2-MOD-HD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-SE-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A2-MOD-HX-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NCS-55A2-MOD-SE-H-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.1	IOS XR 6.6.1
NCS-55A1-48Q6H	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
NCS-55A1-24Q6H-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-24Q6H-SS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • For QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-32T16Q4H-A	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.2	IOS XR 7.2.2
NC57-36H-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.8.1	IOS XR 7.8.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57B1-6D24H-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57B1-5D24-SE	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57C3-MOD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NCS-57C3-MOD-SE-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
NC57-36H6D-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.2	IOS XR 7.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-5502-E	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC57-MOD-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NCS-57C1-48Q6-SYS	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2
NC57-MPA-12L-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.6.1	IOS XR 7.6.1
NC55-OIP-02	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.7.1	IOS XR 7.7.1
Network Device Notes for above line : • Supported on NCS-57C3 and NCS-55A2													
NC57-48Q2D-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NC57-48Q2D-SE-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.10.1	IOS XR 7.10.1
NCS-57C1-48Q6D-S	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2