

Cisco SFP-10G-ZR-S Compatibility Matrix Datasheet



Click here to buy our
compatible transceiver

[BUY NOW](#)

C2960S
C2960X
C2960XR
C9400
C9500
N3500
N5000
N7000
UCSB
NCS5500
FPRHIGH
FPRUHI
C3560CX
C6800
FPRMID
C4900
N9300
N3000
C9300
N9500
N9200
ASR9000
ASR1000
ASR903
ASR920
NCS4200
C4500
C4500X
C3850
C3750X
C3650
C3560X
NCS540

C2960S
 NCS560
 C9200
 C9200L
 C9600
 C9300L
 N9800
 N7700
 C8500
 C9300X
 UCSX
 C9400X
 C9200CX
 C9300LM
 FPRLOW
 CSF4200
 FPRMID3

C9300L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300L-24UXG-2Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required.													
C9300L-24T-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48T-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24P-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-48P-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.1	IOS XE 16.12.1
C9300L-24UXG-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
C9300L-48UXG-2Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.1.1	IOS XE 17.1.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required.													
C9300L-48PF-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2

ASR9000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-9001	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-4T16GE-TR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A9K-4T16GE-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
ASR-9001-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.1	IOS XR 6.2.1
A9K-24X10GE-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.3	IOS XR 6.1.3
A9K-24X10GE-TR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.3	IOS XR 6.1.3
A9K-MPA-8X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD400													
A9K-MPA-8X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.2	IOS XR 64 Bit 6.3.2
Network Device Notes for above line : • On MOD200													
A9K-MPA-8X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-8X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-24X10GE-1G-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-24X10GE-1G-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-24X10GE-1G-TR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-24X10GE-1G-TR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-48X10GE-1G-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-48X10GE-1G-TR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.2.2	IOS XR 64 Bit 6.2.2
A9K-MPA-20X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200													
A9K-MPA-20X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.3.1	IOS XR 64 Bit 6.3.1
Network Device Notes for above line : • On MOD200													
A99-48X10GE-1G-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-TR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 Bit 6.5.2	IOS XR 64 Bit 6.5.2
A99-48X10GE-1G-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.5.2	IOS XR 64 bit 6.5.2
A9K-24X10GE-1G-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.2	IOS XR 64 bit 6.2.2
A9K-24X10GE-1G-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
A9K-MPA-8X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD400													
A9K-MPA-8X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.2	IOS XR 64 bit 6.3.2
Network Device Notes for above line : • On MOD200													
A9K-MPA-8X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-8X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200 and MOD400.													
A9K-MPA-20X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD200													
A9K-MPA-20X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.1.1	IOS XR 6.1.1
Network Device Notes for above line : • On MOD200.													
A9K-MPA-20X10GE-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.3.1	IOS XR 64 bit 6.3.1
Network Device Notes for above line : • On MOD200													
A9K-MPA-48X10GE-1G-FC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 64 bit 6.2.2	IOS XR 64 bit 6.2.2

CSF4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-4215	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-4225	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-4245	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

N7000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M132XP-12L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(1)	NX-OS 6.1(1)

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N7K-M224XP-23L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(1)	NX-OS 6.1(1)
N7K-F312FQ-25	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
N7K-F132XP-15	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(1)	NX-OS 6.1(1)
N7K-F248XP-25	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(1)	NX-OS 6.1(1)
N7K-F248XP-25E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)	NX-OS 6.1(2)
N7K-F348XP-25	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(12)	NX-OS 6.2(12)
N7K-M348XP-25L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)
N7K-M324FQ-25L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)

NCS540

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N540-24Z8Q2C-SYS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Supported on SFP10 ports 0-23 only													
N540-ACC-SYS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Supported on SFP10 ports 0-23 only													
N540X-ACC-SYS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • Supported on SFP10 ports 0-23 only													
N540X-16Z4G8Q2C-A	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
Network Device Notes for above line : • Supported on SFP10 ports 4-19 only													
N540X-16Z4G8Q2C-D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
Network Device Notes for above line : • Supported on SFP10 ports 4-19 only													
N540X-12Z16G-SYS-A	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
Network Device Notes for above line : • Supported on SFP10 ports 4-19 only													
N540X-12Z16G-SYS-D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.1.1	IOS XR 7.1.1
Network Device Notes for above line : • Supported on SFP10 ports 4-19 only													
N540X-4Z14G2Q-A	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540X-4Z14G2Q-D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1
N540X-16Z8Q2C-D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.5.2	IOS XR 7.5.2

N3000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3232C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C36180YC-R	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N3K-C3064PQ-10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)U3(2b)	NX-OS 5.0(3)U3(2b)
Network Device Notes for above line : • Native SFP+ ports													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3064PQ-10GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3064PQ-10GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	—
N3K-C3132Q-40GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • SFP Port													
N3K-C3132Q-40GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3132Q-40GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3132Q-40GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3132Q-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
Network Device Notes for above line : • For native SFP+ ports only.													
N3K-C3132Q-V	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • For native SFP+ ports only.													
N3K-C3172TQ-32T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3172PQ-10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C3172PQ-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
N3K-C3172TQ-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(2)	NX-OS 7.0(3)I2(2)
N3K-C31108PC-V	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C31108TC-V	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
N3K-C31128PQ-10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3264Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I4(1)	NX-OS 7.0(3)I4(1)
Network Device Notes for above line : • Native SFP+ ports													
N3K-C3048TP-1GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1a)	NX-OS 7.0(3)I2(1a)
N3K-C3264C-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(1)	NX-OS 9.2(1)
Network Device Notes for above line : • For QSFP Ports (1-64), QSA (CVR-QSFP-SFP10G) required.													
N3K-C3132C-Z	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2)	NX-OS 9.2(2)
Network Device Notes for above line : • For QSFP Ports (1-32), QSA (CVR-QSFP-SFP10G) required.													
N3K-C34180YC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2.2	—
Network Device Notes for above line : • SFP Ports (1-48).													
N3K-C34200YC-SM	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(2V)	NX-OS 9.2(2V)
Network Device Notes for above line : • SFP Ports (1-48).													

N9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C93180YC-EX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0314.2	NX-OS 70314.2
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C93180YC-EX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.3(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C93180YC-FX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C93180YC-FX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(2)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C9348GC-FXP	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	NX-OS 70317.1
Network Device Notes for above line : • Supported on ports 49 - 52 only													
N9K-C9348GC-FXP	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (49-52).													
N9K-C93240YC-FX2	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.3	NX-OS 70317.3
Network Device Notes for above line : • SFP Ports (1-48). Breakout not supported.													
N9K-C93240YC-FX2	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-M12PQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.1(2)I3(3)	NX-OS 6.1(2)I3(3)
N9K-C9372PX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I1(2)	—
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C9372PX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C9372PX-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I2(1)	NX-OS 7.0(3)I2(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C9372PX-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.1(2h)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (1-48).													
N9K-C93180LC-EX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-12.2(1)	ACI-N9KDK9-13.0(1)
N9K-C93180LC-EX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 70317.1	—
N9K-C9364C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-13.0(1)	ACI-N9KDK9-13.0(1)
Network Device Notes for above line : • SFP Ports (65-66).													
N9K-C9396PX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I1(2)	—
N9K-C9396PX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-11.0(3f)	ACI-N9KDK9-13.0(1)
N9K-C9332C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.0(1)	ACI-N9KDK9-14.0(1)
Network Device Notes for above line : • SFP Ports (33-34).													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C9332C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.2(3)	NX-OS 9.2(3)
Network Device Notes for above line : • SFP Ports (33-34).													
N9K-C93360YC-FX2	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.1	NX-OS 9.3.1
Network Device Notes for above line : • SFP Ports (1-96).													
N9K-C93360YC-FX2	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.1(2)	ACI-N9KDK9-14.1(2)
Network Device Notes for above line : • SFP Ports (1-96).													
N9K-C9364C-GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-14.2(3)	ACI-N9KDK9-14.2(3)
N9K-C93180YC-FX3S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(5)	NX-OS 9.3(5)
Network Device Notes for above line : • a) SFP Ports (1-48). SyncE: network device and optic combination tested. b) QSFP Ports (49-54), QSA (CVR-QSFP-SFP10G) required.													
N9K-C93180YC-FX3	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • Supported on ports 1-48 only. SyncE: network device and optic combination tested for ACI-N9KDK9-15.2.x onwards													
N9K-C93180YC-FX3	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(7)	NX-OS 9.3(7)
Network Device Notes for above line : • Supported on ports 1-48 only. SyncE: network device and optic combination tested													
N9K-C93108TC-FX3P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3.5	NX-OS 9.3.5
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C93108TC-FX3P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-15.1(3)	ACI-N9KDK9-15.1(3)
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
N9K-C9332D-GX2B	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Network Device Notes for above line : • Only on 2 SFP+ ports													
N9K-C9348D-GX2A	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Network Device Notes for above line : • Only on 2 SFP+ ports													
N9K-C9364D-GX2A	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Network Device Notes for above line : • Only on 2 SFP+ ports													
N9K-C9348GC-FX3	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C9348GC-FX3	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
N9K-C9348GC-FX3PH	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(1)	NX-OS 10.4(1)
N9K-C93108TC-FX3	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.4(2)F	NX-OS 10.4(2)F
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) or QSA (CVR-QSFP-SFP10G) is required													
N9K-C93108TC-FX3	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(5)	ACI-N9KDK9-16.0(5)
Network Device Notes for above line : • For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) or QSA (CVR-QSFP-SFP10G) is required													

ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR1002-HX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1001-HX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
EPA-10X10GE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1

N9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X97160YC-EX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I5(2)	NX-OS 7.0(3)I5(2)
Network Device Notes for above line : • 1) SFP ports (1-48) 2) QSFP ports (49-52), QSA (CVR-QSFP-SFP10G) required.													
N9K-X9564PX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I1(2)	—
Network Device Notes for above line : • Downlinks.													
N9K-X9464PX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I1(2)	—
N9K-X96136YC-R	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 9.3(3)	NX-OS 9.3(3)
N9K-X9716D-GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.1(1)	NX-OS 10.1(1)
Network Device Notes for above line : • For QSFP-DD and QSFP28 Ports, QSA (CVR-QSFP-SFP10G) required													
N9K-X9400-8D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Network Device Notes for above line : • Only on 2 SFP+ ports													
N9K-X9400-8D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
Network Device Notes for above line : • Please see release note or configuration guide for 10G with QSA consideration													
N9K-X9400-16W	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(2)	NX-OS 10.3(2)
Network Device Notes for above line : • Only on 2 SFP+ ports													
N9K-X9400-16W	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	ACI-N9KDK9-16.0(2h)	ACI-N9KDK9-16.0(2h)
Network Device Notes for above line : • Please see release note or configuration guide for 10G with QSA consideration													

C9300X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300X-12Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-2C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. QSA28 (CVR-QSFP28-SFP25G) can also be used from IOS XE 17.12.1. Uplink module for C9300X models only													
C9300X-24Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-8Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.5.1	IOS XE 17.5.1
C9300X-NM-4C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.6.1	IOS XE 17.6.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • For QSFP ports, QSA (CVR-QSFP-SFP10G) required. QSA28 (CVR-QSFP28-SFP25G) can also be used from IOS XE 17.12.1. Uplink module C9300X-NM-4C is supported in the C9300X-48HX, C9300X-48TX and C9300X-24Y.													

C9500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9500-24Y4C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-24; QSFP Ports 25-28: QSA (CVR-QSFP-SFP10G) required.													
C9500-24Y4C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-24													
C9500-48Y4C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
Network Device Notes for above line : • SFP Ports 1-48; QSFP Ports 49-52: QSA (CVR-QSFP-SFP10G) required.													
C9500-48Y4C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • SFP Ports 1-48													
C9500-12Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-24Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.5.1a
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-40X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-NM-2Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-32QC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-32C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
Network Device Notes for above line : • QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9500-NM-8X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9500-16X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.8.1	IOS XE 16.8.1
C9500X-28C8D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													
C9500X-60L4D	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.10.1	IOS XE 17.10.1
Network Device Notes for above line : • For QSFP28 and QSFP-DD ports, QSA (CVR-QSFP-SFP10G) is required													

C9300

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-8X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.5.1	IOS XE 16.5.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300-NM-2Q	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1

Network Device Notes for above line :
• For QSFP ports, QSA (CVR-QSFP-SFP10G) required. Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN

NCS4200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NCS4200-1T8LR-PS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
NCS4201-SA	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
NCS 4201-SA	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	
NCS4200-8T-PS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
NCS4202-SA	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17

C4500X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4500X-32SFP+	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-F-32SFP+	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-F-32SFP+	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
C4KX-NM-8SFP+	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0SG	IOS 3.0SG
WS-C4500X-16SFP+	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG
WS-C4500X-F-16SFP+	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG
WS-C4500X-24X-ES	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.1SG	IOS 3.1SG

C2960XR

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960XR-24TD-I	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960XR-48TD-I	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960XR-24PD-I	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960XR-48LPD-I	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960XR-48FPD-I	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3

ASR903

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA8S1Z	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
A900-IMA8T1Z	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
A900-IMA2Z	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	
A900-IMA8Z	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.17.0S	

C9200L

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200L-24P-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48P-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24T-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48T-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.2	IOS XE 16.9.2
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-24PXG-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PXG-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • On board - fixed uplinks													
C9200L-48PL-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1

C4900

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C4948E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SG	IOS 15.0(2)SG
WS-C4948E-F	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.0(2)SG	IOS 15.0(2)SG

NCS560

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
A900-IMA-8Z	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.6.25	IOS XR 6.6.25
A900-IMA-8Z-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
N560-IMA-8Q/4L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.4.1	IOS XR 7.4.1

N9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-C92160YC-X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I3.1	NX-OS 7.0(3)I3.1
N9K-C92300YC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 703I6.1	NX-OS 703I6.1

N9800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N9K-X9836DM-A	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 10.3(3)F	NX-OS 10.3(3)F

C3650

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3650-12X48UZ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-24TD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48TD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-24PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-24PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-24PDM	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48FD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48PQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48PQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-48TQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48TQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 16.1.1	IOS 16.1.1
WS-C3650-8X24PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
WS-C3650-8X24UQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-12X48UQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-12X48UR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48FQM	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
WS-C3650-48FQ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE

N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N5K-C5672UP-16G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(2)N1(1)	
Network Device Notes for above line : • On only 16x UP ports													
N5K-C5672UP	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.3(2)N1(1)	
Network Device Notes for above line : • On only 16x UP ports													

N7700

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N77-M324FQ-25L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													
N77-F324FQ-25	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.2(1)	NX-OS 8.2(1)
N77-M312CQ-26L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													
N77-F248XP-23E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(2)	NX-OS 6.2(2)
N77-F348XP-23	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.2(6)	NX-OS 6.2(6)
N77-M348XP-23L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.0(1)	NX-OS 8.0(1)
N77-F430CQ-36	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 8.4(2)	NX-OS 8.4(2)
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) min V02 required. To bring up the link with CVR-QSFP-SFP10G adapter in a M3/F4 100G module, you need to perform the 4X10G breakout configuration on the interface. In older release versions with CVR-QSFP-SFP10G, the adapter link remains down. After ISSU to Cisco NX-OS Release 8.4(2) the link will still remain down. Perform OIR to bring up the link.													

C8500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C8500-12X4QC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500-12X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.2	IOS XE 17.3.2
C8500L-8S4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.4.1	IOS XE 17.4.1
C8500-20X6C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.4.1	IOS XE 17.10.1

C3850

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-48F	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3850-48XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.2	IOS XE 3.7.2
WS-C3850-48XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2.1	IOS XE 16.2.1
WS-C3850-48T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-48P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-24T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G uplink modules													
WS-C3850-12S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-24S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.3.3SE	IOS XE 3.3.3SE
Network Device Notes for above line : • With C3850-NM-2-10G or C3850-NM-4-10G or C3850-NM-8-10G uplink modules													
WS-C3850-12XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-4-10G network module													
WS-C3850-12XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-16XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
WS-C3850-24XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.1.1	IOS XE 16.1.1
WS-C3850-32XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.7.1E	IOS XE 3.7.1E
Network Device Notes for above line : • With C3850-NM-8-10G uplink modules													
C3850-NM-2-10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-4-10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													
C3850-NM-8-10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • Uplink module for C9300- 24T/48T/24P/48P/24U/48U/24UX/48UXM/48UN with minimum software of IOS XE 16.6.1.													

C6800

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-32P10G-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-16P10G-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-8P10G-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C6800-32P10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-16P10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-8P10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6800-SUP6T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.3(1)SY
C6800-SUP6T-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.3(1)SY	IOS 15.3(1)SY
C6880-X-LE-16P10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6880-X-16P10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6800IA-48FPDR	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)SY	IOS 15.2(1)SY
C6880-X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1
C6880-X-LE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.1(2)SY1	IOS 15.1(2)SY1

C4500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-X45-SUP9-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.10	IOS XE 3.10
WS-X4712-SFP+E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0SG	IOS 3.2.0SG
WS-X45-SUP7-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0SG	IOS 3.2.0SG
WS-X45-SUP7L-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.2.0XO	IOS 3.2.0XO
WS-X45-SUP8-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.0XO	IOS 3.0XO
WS-X45-SUP8L-E	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.8.1E	IOS 3.8.1E

FPRMID3

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR3K-XNM-8X25G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
3130	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
3140	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR3K-XNM-8X10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3105	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3110	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
3120	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

C9200CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200CX-8P-2X2G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12P-2X2G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-12T-2X2G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9200CX-8UXG-2X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4
C9200CX-8UXG-2XH	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.4	IOS XE 17.9.4

FPRUHI

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR9K-SM-24	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower	

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
												product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-36	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-40	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-44	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-48	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR9K-SM-56	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

N3500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N3K-C3524P-10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3548P-10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3524P-10GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3548P-10GX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 6.0(2)A6(8)	NX-OS 6.0(2)A6(8)
N3K-C3548P-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(3)	NX-OS 7.0(3)I7(3)
N3K-C3524P-XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 7.0(3)I7(3)	NX-OS 7.0(3)I7(3)

C9400

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400-SUP-1	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
C9400-SUP-1XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-LC-24XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.2	IOS XE 16.6.2
C9400-SUP-1XL-Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
C9400-LC-48XS	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
C9400-LC-24XY	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1
C9400-LC-12QC	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.12.1	IOS XE 17.12.1

Network Device Notes for above line :

- For QSFP ports, QSA28 (CVR-QSFP28-SFP25G) required.

UCSX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCSX-FI-6454-U	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCSX-FI-64108-U	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

C9200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9200-NM-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.10.1	IOS XE 16.10.1

Network Device Notes for above line :

- Uplink module for C9200-24P/48P/24T/48T

C9200-NM-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.12.2	IOS XE 16.12.2
-------------	--------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	----------------	----------------

Network Device Notes for above line :

- Uplink module for C9200-24PXG; C9200-48PXG

C9200-NM-4X	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.3.1	IOS XE 17.3.1
-------------	--------------	-----	---------	------	------	--------------	-----	----------------	-------	----------	---	---------------	---------------

Network Device Notes for above line :

- Uplink module for C9200-48PL

C3560CX

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560CX-12PD-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(4)E2	IOS 15.2(4)E2
WS-C3560CX-8XPD-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(4)E2	IOS 15.2(4)E2

FPRMID

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-2130	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
FPR-2140	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	

C2960X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C2960X-HYBRID-STK	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
C2960X-HYBRID-STK	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.10.0E	IOS 3.10.0E
C2960X-FIBER-STK	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(6)E	IOS 15.2(6)E
C2960X-FIBER-STK	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 3.10.0E	IOS 3.10.0E
WS-C2960X-24TD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960X-24PD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960X-48TD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960X-48LPD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3
WS-C2960X-48FPD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(2)E3	IOS 15.2(2)E3

C3560X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3560X-24T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-48T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-24P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-48P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3560X-48PF	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													

C9600

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9600-LC-48YL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600-LC-48YL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													
C9600-LC-24C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
Network Device Notes for above line : • When in use with C9600-SUP-1. QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9600-LC-24C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. QSFP Ports: QSA (CVR-QSFP-SFP10G) required.													
C9600-LC-40YL4CD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. QSA (CVR-QSFP-SFP10G) supported from IOS XE 17.11.1 required for use in QSFP ports													
C9600-LC-40YL4CD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.8.1	IOS XE 17.8.1
Network Device Notes for above line : • When in use with C9600-SUP-1.													
C9600X-LC-32CD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.11.1	IOS XE 17.11.1
Network Device Notes for above line : • When in use with C9600X-SUP-2. For QSFP ports, QSA (CVR-QSFP-SFP10G) is required.													
C9600X-LC-56YL4C	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.13.1	IOS XE 17.13.1
Network Device Notes for above line : • When in use with C9600X-SUP-2.													

C9400X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9400X-SUP-2	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1
C9400X-SUP-2XL	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.7.1	IOS XE 17.7.1

C3750X

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C3750X-24T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48T	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-24P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48P	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-48PF	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-12S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													
WS-C3750X-24S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
Network Device Notes for above line : • With network modules C3KX-SM-10G (support either 1-Gigabit SFP or 10-Gigabit SFP+ modules) and C3KX-NM-10G (Slots 1, 2, 3, and 4 with 1-Gigabit SFP modules; Slots 1 and 2 with 1-Gigabit SFP modules and Slot 4 with one 10-Gigabit SFP+ module; Slot 2 with one 10-Gigabit SFP+ module and Slots 3 and 4 with 1-Gigabit SFP modules; Slot 2 and Slot 4 each with 10-Gigabit SFP+ modules)													

FPRLOW

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR-1150	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets, installation guides, and release notes for software configurations.	
Network Device Notes for above line : • Two of the SFP ports (ports 9 and 11) support 10 Gb/s data rate.													

C9300LM

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C9300LM-24U-4Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48U-4Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48UX-4Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1
C9300LM-48T-4Y	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 17.9.1	IOS XE 17.9.1

ASR920

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR-920-10SZ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-12CZ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-12SZ-IM	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-24SZ-M	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-24SZ-IM	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-4SZ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-24TZ-M	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-12SZ	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.9.1	IOS XE 16.9.1
ASR-920-20SZ-M	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR-920-10SZ-PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17
ASR-920-8S4Z-PD	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 3.17	IOS XE 3.17

FPRHIGH

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
FPR4K-XNM-8X10G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	
FPR4K-XNM-8X25G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please refer to Firepower product datasheets ; installation guides, and release notes for software configurations.	

UCSB

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
UCS-FI-6454	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-64108-U	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)
UCS-FI-6454-U	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	UCS Manager v4.0(1a)	UCS Manager v4.0(1a)

NCS5500

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
NC55-36X100G	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-24X100G-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-24H12F-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC55-36X100G-A-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.3.2	IOS XR 6.3.2
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-5501-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.2.2	IOS XR 6.2.2
Network Device Notes for above line : • Supported on ports 16 to 39 only.													
NCS-5502	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-5502-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-36H-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NCS-55A1-24H	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.2.1	IOS XR 7.2.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-55A1-36H-SE-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.3.1	IOS XR 7.3.1
NC55-MPA-12T-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 6.5.1	IOS XR 6.5.1
NC57-36H-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.9.1	IOS XR 7.9.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57B1-6D24H-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.9.1	IOS XR 7.9.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NCS-57B1-5D24-SE	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.9.1	IOS XR 7.9.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													
NC57-36H6D-S	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XR 7.9.1	IOS XR 7.9.1
Network Device Notes for above line : • QSFP Ports, QSA (CVR-QSFP-SFP10G) required													

C2960S

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
WS-C2960S-48FPD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
WS-C2960S-48LPD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
WS-C2960S-24PD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
WS-C2960S-48TD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E
WS-C2960S-24TD-L	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS 15.2(1)E	IOS 15.2(1)E