

Buy compatible transceivers for this device at

 Compufox.com

UniFi[®] Network Gateway Pro

Datasheet
UXG-Pro

Next-Generation Gateway Pro



Mechanical

Dimensions	442.4 x 43.7 x 285.6 mm (17.42 x 1.72 x 11.24")
Weight	3.42 kg (7.54 lb)
Enclosure materials	Front panel: aluminum CNC Top cover/base: SGCC steel

Hardware

Processor	Quad-core ARM® Cortex®-A57 at 1.7 GHz				
Memory information	2 GB DDR4				
Management interface	Ethernet				
Networking interface	LAN: (1) 1 GbE RJ45 port (1) 10G SFP+ port WAN: (1) 1 GbE RJ45 port (1) 10G SFP+ port				
LCM display	(1) 1.3" touchscreen Bootup animation: bootup in progress Firmware upgrade icon: firmware upgrading				
Button	Factory reset				
Power method	<table border="1"> <tr> <td>US</td> <td>(1) Universal AC input, 125V AC, 2.7A max., 60 Hz (1) RPS DC input, 11.5V DC, 2.87A</td> </tr> <tr> <td>Worldwide</td> <td>(1) Universal AC input, 200–240V AC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5V DC, 2.87A</td> </tr> </table>	US	(1) Universal AC input, 125V AC, 2.7A max., 60 Hz (1) RPS DC input, 11.5V DC, 2.87A	Worldwide	(1) Universal AC input, 200–240V AC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5V DC, 2.87A
US	(1) Universal AC input, 125V AC, 2.7A max., 60 Hz (1) RPS DC input, 11.5V DC, 2.87A				
Worldwide	(1) Universal AC input, 200–240V AC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5V DC, 2.87A				
Power supply	AC/DC, internal, 50W				
Max. power consumption	30W				
ESD/EMP protection	Air: ± 15 kV, contact: ± 8 kV				
Operating temperature	-10 to 40° C (14 to 104° F)				
Operating humidity	5 to 95% noncondensing				
Certifications	CE, FCC, IC				

LEDs

AC outlet/ RPS	Blue
Ethernet	Green/amber
SFP+	White/green

